

# Special Application Commercial Gate Single Phase, Permanent Split Capacitor Open Dripproof (ODP)



## APPLICATIONS:

Designed for gate openers, hoists and most medium start reversing applications.

## FEATURES:

- 40°C Ambient
- 1.0 Service Factor
- Reversible Rotation
- 115 Volt, 60 Hertz
- Permanent Lubricated Ball Bearings
- 3 Lead Connection
- Terminal Board Connections/Without Motor Switch
- Lower Inrush And Operating Currents
- Modest Starting Torque
- Allows Frequent Starts
- Continuous Duty Capacitor
- Continuous Duty/Intermittent Duty (1 HP Intermittent)

## Rigid Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1800	115	56	D13ARM2N	\$290	DS-3FMP	1.00	10.4	18	3.9-4.2	23
1/2	1800	115	56	D12ARM2N	\$322	DS-3FMP	1.00	10.4	19	5.0-5.7	23
3/4	1800	115	56	D34ARM2N	\$387	DS-3FMP	1.00	11.9	26	8.0-8.3	23

## C-Face Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1	1800	115	56C	D1ARA2NC	\$375	DS-3FMP	1.00	10.9	23	10.3-16.3	24

## C-Face Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1800	115	56C	D13ARM2NCR	\$266	DS-3FMP	1.00	9.9	18	3.9-4.2	23
1/2	1800	115	56C	D12ARM2NCR	\$298	DS-3FMP	1.00	9.9	19	5.0-5.7	23
3/4	1800	115	56C	D34ARM2NCR	\$324	DS-3FMP	1.00	11.4	26	8.0-8.3	23

## Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1800	115	56	D13ARM2N9	\$304	DS-3FMP	1.00	10.8	19	3.9-4.2	23, 35
1/2	1800	115	56	D12ARM2N9	\$341	DS-3FMP	1.00	10.8	18	5.0-5.7	23, 35
3/4	1800	115	56	D34ARM2N9	\$405	DS-3FMP	1.00	12.3	26	8.0-8.3	23, 35

Note 23 Manual Reset Thermal Overload Protector

Note 24 Automatic Reset Thermal Overload Protector

Note 35 Resilient Base