

# Special Application Single Phase, Open Dripproof (ODP) Jet Pump, Square Flange Capacitor Start



## APPLICATIONS:

Designed for jet pumps, booster pumps, centrifugal pumps, lawn sprinkler pumps.

## FEATURES:

- 416 Stainless Steel Shaft
- Shaft Threads: 1/2-20 UNC-2A, 0.625" Diameter, 0.91" Long
- Ball Bearings (Locked Drive End Bearing)
- Continuous Duty
- 60 Hertz
- E-Z Access® Cover (On Two Compartment Designs)
- 40C Ambient
- Automatic Reset Thermal Overload Protector
- Round Frame (Without Base), Square Flange Mounting
- Power Leads Supplied For Proper Connection To Pressure Switch
- Voltage Selector Switch (Catalog Numbers Ending With "-2V")

## Two Compartment Product, E-Z Access®

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/2	3600	115/230	56Y	JS0502-2V	\$139	DS-3FJP	1.90	11.6	17	0	8.6/4.3	-
3/4	3600	115/230	56Y	JS0752-2V	\$161	DS-3FJP	1.65	11.9	20	0	5.8/11.6	-
1	3600	115/230	56YZ	JS1002-2V	\$185	DS-3FJP	1.65	12.4	22	0	13.6/6.8	-
1-1/2	3600	115/230	56YZ	JS1502-2V	\$210	DS-3FJP	1.50	12.9	24	0	14.4/7.2	18
2	3600	230	56YZ	JS2002-2	\$241	DS-3FJP	1.30	12.9	25	0	8.6	18

## Single Compartment Product

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/3	3600	115	56Y	JS0332-1	\$118	DS-3FJP	1.95	10.3	13	0	6.6	94
1/2	3600	115/230	56Y	JS0502-1	\$130	DS-3FJP	1.90	10.8	17	0	8.4/4.2	-
3/4	3600	115/230	56Y	JS0752-1	\$152	DS-3FJP	1.65	11.0	19	0	11.6/5.8	-
1	3600	115/230	56YZ	JS1002-1	\$175	DS-3FJP	1.65	11.5	22	0	13.6/6.8	-
1-1/2	3600	115/230	56YZ	JS1502-1	\$200	DS-3FJP	1.50	12.0	25	0	14.4/7.2	18
2	3600	230	56YZ	JS2002-1	\$235	DS-3FJP	1.30	12.0	25	0	8.6	18

Note 18 Incorporates Run Capacitor

Note 94 Split Phase