

Direct Drive Blower Permanent Split Capacitor Totally Enclosed Air Over (TEAO) Resilient/Stud Mount



APPLICATIONS:

Designed for use in exhaust and poultry fans, air circulators and other direct drive fans.

FEATURES:

- Supplied with Capacitor Mounted
- Totally Enclosed Construction for Dirty or Dusty Environments
- Shaft Dimension 0.50" Dia. x 2.5" Long
- Class A Insulation except where noted
- Automatic Reset Thermal Overload Protector
- Extended Studs for Mounting Fan Guard
- Reversible Rotation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1075	115	48Z	4812	\$120	DS-3FMP	1.00	10.4	18	3.3	99
	1075	115	48Z	4814	\$130	DS-3FMP	1.00	9.9	15	3.4	B, BB
1/3	1075	115	48Z	4815	\$123	DS-3FMP	1.00	12.9	18	4.6	61
1/2	1075	115	48Z	4816	\$137	DS-3FMP	1.00	10.9	21	7.0	61

Note 61 Sleeve Bearings
Note 99 Two Speed

Note B Class B Insulation
Note BB Ball Bearings