

Permanent Split Capacitor & Shaded Pole Flex Mount Direct Drive Fan & Blower 5.0" & 5.6" Diameter, Open, Air Over



APPLICATIONS:

Designed for use on direct drive fan & blowers with flexible ear mounts.

FEATURES:

- Class B Insulation Unless Noted
- 5.0" Diameter Motors CWLE Rotation
- 5.6" Diameter Motors Reversible Rotation
- Sleeve Bearings, All Angle Thrust System
- Continuous Duty, Air Over
- 24" Leads
- Automatic Reset Thermal Overload Protector
- PSC Motors Designed For 370V Capacitors
- Discount Symbol: DS-3HAC

Permanent Split Capacitor 5.6" Diameter

HP	RPM/Spd.	Volts	Catalog Number	List Price	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Cap Mfd.	Notes	OEM
1/6	1075/3	115	3782	\$90	3.0	5.0	3.8	8.8	9	-	LA	
1/4	1075/3	115	3783	\$96	3.8	5.0	4.3	9.3	11	5.0		
	1075/3	208-230	3784	\$99	1.7	5.0	4.3	9.3	10	5.0		
1/3	825/3	230	8052	\$149	1.9	2.5	4.8	7.3	14	15.0		LE
	1000/4	115	9377	\$99	6.0	5.3	4.6	9.8	13	5.0		
	1075	115	1054	\$134	4.2	5.0	3.8	8.8	12	-	LA	
	1075/3	115	2482	\$90	-	-	-	-	-	-	LA	
	1075/3	115	3785	\$100	5.0	5.0	4.6	9.6	13	7.5		
	1075/3	208-230	3786	\$103	2.4	5.0	4.3	9.3	12	5.0		
1/2	1075/3	115	3787	\$119	7.5	5.0	5.6	10.7	18	10.0		
	1075/3	208-230	3788	\$123	3.3	5.0	5.3	10.3	17	7.5		