


Permanent Split Capacitor Ventilation Direct Drive Blower

5.6" & 6.3" Diameter, Totally Enclosed, Air Over (TEAO)



APPLICATIONS:

Design for direct drive ventilation units requiring a totally enclosed motor.

FEATURES:

- Continuous Duty
- 1/2" Dia. x 2 1/2" Shaft
- Reversible Rotation
- Studs For Mounting Fan Guard
- Terminal Board With Side Conduit Plug
- Automatic Thermal Protection
- Includes Capacitor Mounted With Cover
- Discount Symbol: DS-3HAC

HP	RPM/Spd.	Volts	NEMA Frame	Catalog Number	List Price	Amps	Eff.	SF	Bearings	Insul. Class	Total Length	Ship Wgt.	Notes	OEM
1/6	1725	115	48Y	8499	\$119	3.5	Std	-	Ball	-	8.4	19	LA	
1/4	1020	115	48Y	4153	\$175	4.5	Std	1.0	Slv	B	10.0	8.5		MQ
	1075/2	115	48Z	4812	\$169	3.3	Std	1.0	Slv	A	9.9	18		
	1075	115	48Z	4814	\$163	3.4	High	1.0	Ball	B	9.9	15		
	1725	115	56Z	6326	\$183	5.0	Std	1.0	Ball	A	9.8	18	1	
1/3	1075	115	48Z	4815	\$154	4.6	High	1.0	Slv	A	10.5	18		
	1725	115	48Z	8511	\$155	5.2	Std	1.0	Ball	B	10.2	15	1	
	1725	115	56Z	6328	\$224	5.4	Std	1.0	Ball	A	9.8	21	1	
1/2	1075	115	48Z	4816	\$171	7.0	High	1.0	Slv	B	10.9	2		
	1725	115	56Z	6330	\$236	7.4	Std	1.0	Ball	A	10.3	23	1	
	1700	115/230	48Z	1850	\$219	5.0/2.5	High	1.0	Ball	B	10.9	25		

UL 507 Specification Blower, TEAO, Split Phase, Resilient Stud Mount

HP	RPM	Volts	NEMA Frame	Catalog Number	List Price	Amps	Shaft Length	Shaft Dia.	Bearings	Protector	Total Length	Ship Wgt.	Notes
1/4	1800	115	56Z	4819	\$144	Slv	4.8	1.5	0.5	Man	8.9	18	LA
	1800	115	56Z	4820	\$163	Ball	4.8	1.5	0.5	Man	8.9	28	LA
1/3	1800	115	56Z	4823	\$191	Ball	5.5	1.5	0.5	Man	8.9	20	LA
1/2	1800	115	56	4825	\$269	Slv	7.0	1.875	0.625	Man	10.3	28	LA

Note 1 Split Phase