

General Purpose Single Phase Hazardous Location Class I (Group C & D), Class II (Group E, F & G)



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment located in hazardous areas.

FEATURES:

- UL[®] Listed & CSA[®] Certified
- Temp Code T3C
- Class B Insulation
- Continuous Duty
- 40°C Ambient Rated
- F1 Assembly

Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/208-230&110/220	56	XS14CA2J	\$310	DS-3F	1.00	12.5	31	5.1/2.5-2.5&5.6/2.8	24, 98
	1200	115/230	56	XS14CA3P	\$454	DS-3F	1.00	13.0	22	6.8/3.4	24
1/3	3600	115/208-230	56	XS13CA1J	\$360	DS-3F	1.00	13.0	29	8.0/3.6-4.0	24
	1800	115/208-230	56	XS13CA2J	\$329	DS-3F	1.00	12.7	32	6.8/3.3-3.4	24
	1200	115/230	56	XS13CA3P	\$586	DS-3F	1.00	13.0	31	7.2/3.6	24
1/2	3600	115/230	56	XS12CA1P	\$391	DS-3F	1.00	13.0	30	8.0/4.0	24, LA
	3600	115/208-230	56	XS12CA1J	\$391	DS-3F	1.00	13.0	29	8.8/4.1-4.4	24
	1800	115/208-230	56	XS12CA2J	\$362	DS-3F	1.00	13.2	33	9.8/4.9-4.9	24
	1200	115/230	56H	XS12CA3P	\$677	DS-3F	1.00	14.1	40	10.0/5.0	24
3/4	3600	115/208-230	56	XS34CA1J	\$441	DS-3F	1.00	13.0	36	10.4 / 5.3 - 5.2	24
	1800	115/203-230	56	XS34CA2J	\$405	DS-3F	1.00	13.7	38	12.6/6.3-6.3	24
	1200	208-230/460	143T	XS34S3A14	\$375	DS-3F	1.00	15.0	45	3.1-3.2/1.6	-
1	3600	115/208-230	56	XS1CA1J	\$391	DS-3F	1.00	14.2	44	12.0/6.3-6.0	24
	1800	115/230	56H	XS1CA2JH	\$459	DS-3F	1.00	14.2	45	14.0/6.9-7.0	24

C-Face Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/208-230&110/220	56C	XS14CA2JCR	\$310	DS-3F	1.00	11.9	30	5.1/2.5-2.5 & 5.6/2.8	24, 98
1/3	3600	115/208-230	56C	XS13CA1JCR	\$395	DS-3F	1.00	13.3	30	8.0 / 3.6 - 4.0	24
	1800	115/208-230	56C	XS13CA2JCR	\$345	DS-3F	1.00	12.8	31	6.8/3.3-3.4	24
1/2	3600	115/230	56C	XS12CA1PCR	\$438	DS-3F	1.00	13.0	27	8.0/4.0	24, LA
	3600	115/208-230	56C	XS12CA1JCR	\$438	DS-3F	1.00	13.3	31	8.8/4.1-4.4	24
	1800	115/208-230	56C	XS12CA2JCR	\$362	DS-3F	1.00	13.8	32	9.8/4.9-4.9	24
3/4	3600	115/208-230	56C	XS34CA1JCR	\$468	DS-3F	1.00	13.3	35	10.4 / 5.3-5.2	24
	1800	115/208-230	56C	XS34CA2JCR	\$405	DS-3F	1.00	14.0	40	11.4/5.7	24
1	3600	115/208-230	56C	XS1CA1JCR	\$504	DS-3F	1.00	14.3	44	12.0/6.3-6.0	24
	1800	115/208-230	56C	XS1CA2JCR	\$434	DS-3F	1.00	14.8	43	14.0/6.9-7.0	24

Note 24 Automatic Reset Thermal Overload Protector
 Note 25 Non-protected

Note 98 50/60 Hz Motor
 Note LA Limited Availability

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners