

**Super-E and Standard-E, Three Phase, ODP, Foot Mounted**

**1 thru 100 Hp**

**NEMA 143T thru 404T**

**Applications:** Heating, ventilation and air conditioning blower and fan motors.



**Features:** Class F insulated motor with 1.15 service factor or higher that operates within class “B” temperature limits at rated horsepower. Heavy-gauge steel frame construction, ball bearings, grease passages have plugs. Dynamically balanced rotors for reduced vibration and quiet operation. Suitable for mounting in any position. “EHM” models meet NEMA Premium® efficiencies. Inverter Ready and have a 3-year warranty. “HM” models meet EPEA efficiencies.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	“C” Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>F1 Mounting</b>											
1	1800	143T	EHM3116T	481	LS	11.12	34	85.5	208-230/460	1.4	
		143T	HM3116T	311	LS	11.12	31	82.5	208-230/460	1.65	
1 1/2	1800	145T	EHM3154T	500	LS	12.13	38	88.5	208-230-460	2.1	
		145T	HM3154T	330	LS	11.62	39	84	208-230/460	2.2	
2	1800	145T	EHM3157T	539	LS	13.00	46	86.5	208-230/460	2.7	
		145T	HM3157T	357	LS	11.62	41	84	208-230/460	3	
3	1800	182T	EHM3211T	581	LS	15.00	75	90.2	208-230/460	4	
		182T	HM3211T	387	LS	14.00	49	86.5	208-230/460	4.2	
5	1800	184T	EHM3218T	637	LS	16.50	92	90.2	208-230/460	6.6	
		184T	HM3218T	427	LS	15.00	68	87.5	208-230/460	6.9	
7 1/2	1800	213T	EHM3311T	937	LS	16.32	109	91.7	208-230/460	9.6	
		213T	HM3311T	595	LS	17.00	92	88.5	208-230/460	10	
10	1800	215T	EHM3313T	1,133	LS	17.45	124	91.7	208-230/460	12.5	
		215T	HM3313T	746	LS	16.32	108	89.5	208-230/460	13.4	
15	1800	254T	EHM2523T	1,607	LS	21.69	234	93	208-230/460	17.7	
		254T	HM2523T	1,150	LS	19.75	159	91	208-230/460	19	
20	1800	256T	EHM2515T	2,017	LS	21.69	255	93	230/460	23.5	30
		256T	HM2515T	1,374	LS	22.25	235	91.7	230/460	24	30
25	1800	284T	EHM2531T	2,458	LS	23.81	330	94.1	230/460	30	30
		284T	HM2531T	1,699	LS	23.44	226	91.7	230/460	30	30
30	1800	286T	EHM2535T	2,689	LS	25.06	379	94.1	230/460	35	30
		286T	HM2535T	1,962	LS	24.94	249	92.4	230/460	36	30
40	1800	324T	EHM2539T	3,507	LS	26.69	523	94.5	230/460	46	30
		324T	HM2539T	2,530	LS	26.19	340	93	230/460	47.5	30
50	1800	324T	EHM2543T	4,307	LS	27.69	515	94.5	230/460	57	30
		324T	HM2543T	2,933	LS	27.19	378	93	230/460	60.5	30
60	1800	364T	EHM2547T	4,873	LS	29.94	557	95	230/460	68	
		364T	HM2547T	3,621	LS	27.94	479	93.6	230/460	72.5	30
75	1800	365T	EHM2551T	5,982	LS	33.72	616	95	230/460	85	
		365T	HM2551T	4,435	LS	29.94	544	94.1	230/460	88	30
100	1800	404T	EHM2555T	6,821	LS	36.97	552	95.4	230/460	113	
		404T	HM2555T	5,632	LS	35.22	618	94.1	230/460	119	30
<b>F2 Mounting</b>											
1	1800	143T	EHEM3116T	481	LS	11.12	33	85.5	208-230/460	1.4	
		143T	HFM3116T	314	LS	11.12	31	82.5	208-230/460	1.65	
1 1/2	1800	145T	EHEM3154T	503	LS	12.13	41	88.5	208-230-460	2.1	
		145T	HFM3154T	333	LS	11.62	36	84	208-230/460	2.2	
2	1800	145T	EHEM3157T	539	LS	13.00	46	86.5	208-230/460	2.7	
		145T	HFM3157T	361	LS	11.62	41	84	208-230/460	3	
3	1800	182T	EHEM3211T	581	LS	15.00	72	90.2	208-230/460	4	
		182T	HFM3211T	391	LS	14.00	49	86.5	208-230/460	4.2	
5	1800	184T	EHEM3218T	637	LS	16.50	82	90.2	208-230/460	6.6	
		184T	HFM3218T	431	LS	15.00	66	87.5	208-230/460	6.9	
7 1/2	1800	213T	EHEM3311T	937	LS	16.32	112	91.7	208-230/460	9.6	
		213T	HFM3311T	601	LS	17.00	92	88.5	208-230/460	10	

(a) See notes on inside back flap and pages 5-6.

General Information  
Single Phase Motors  
General Purpose Industrial Motors  
Premium Efficient Super-E® Motors  
Severe Duty Motors  
Washdown Duty Motors  
Explosion Proof Motors  
Pump Motors  
Commercial Motors  
HVAC Motors

**Super-E and Standard-E, Three Phase, ODP, Foot Mounted**

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>F2 Mounting (continued)</b>											
10	1800	215T	<b>EHFM3313T</b>	1,133	LS	17.45	134	91.7	208-230/460	12.5	
		215T	<b>HFM3313T</b>	753	LS	16.32	111	89.5	208-230/460	13.4	
15	1800	254T	<b>EHFM2523T</b>	1,607	LS	21.69	245	93	208-230/460	17.7	
		254T	<b>HFM2523T</b>	1,129	LS	19.75	157	91	208-230/460	19	
20	1800	256T	<b>EHFM2515T</b>	2,017	LS	21.69	245	93	230/460	23.5	30
		256T	<b>HFM2515T</b>	1,375	LS	21.69	229	91	230/460	25	30
25	1800	284T	<b>EHFM2531T</b>	2,458	LS	23.81	330	94.1	230/460	30	30
		284T	<b>HFM2531T</b>	1,668	LS	23.44	226	91.7	230/460	30	30
30	1800	286T	<b>EHFM2535T</b>	2,689	LS	25.06	379	94.1	230/460	35	30
		286T	<b>HFM2535T</b>	1,926	LS	24.94	255	92.4	230/460	36	30
40	1800	324T	<b>EHFM2539T</b>	3,507	LS	26.69	479	94.5	230/460	46	30
		324T	<b>HFM2539T</b>	2,484	LS	26.19	365	93	230/460	47.5	30
50	1800	324T	<b>EHFM2543T</b>	3,871	LS	27.69	505	94.5	230/460	57	30
		324T	<b>HFM2543T</b>	2,879	LS	27.19	369	93	230/460	60.5	30
60	1800	364T	<b>EHFM2547T</b>	4,873	LS	30.69	563	95	230/460	68	30
		364T	<b>HFM2547T</b>	3,554	LS	27.94	479	93.6	230/460	72.5	30
75	1800	365T	<b>EHFM2551T</b>	5,982	LS	33.72	616	95	230/460	85	
		365T	<b>HFM2551T</b>	4,353	LS	29.94	544	94.1	230/460	88	30
100	1800	404T	<b>EHFM2555T</b>	6,821	LS	36.97	552	95.4	230/460	113	
		404T	<b>HFM2555T</b>	5,529	LS	35.22	618	94.1	230/460	119	30

(a) See notes on inside back flap and pages 5-6.

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

**HVAC  
Variable Torque,  
Three Phase, ODP**

**1/2 thru 75 Hp**

**NEMA 56 thru 365T**

**Applications:** Heating, ventilation and air conditioning blower and fan motors.



**Features:** Heavy-gauge steel frame construction, ball bearings, 1.15 service factor. Dynamically balanced rotors for reduced vibration and quiet operation. Suitable for mounting in any position. “HM” models meet EPA efficiencies. “EHM” models meet NEMA Premium® efficiencies. H3M and EH3M motors use low profile top-mounted conduit box.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	“C” Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>F1 Mounting</b>											
1	1800	56Z	H3M9210	314	LS	12.13	33	78.5	230/460	1.7	28,30
		56HZ	HM9210	311	LS	12.13	31	78.5	230/460	1.7	30
1 1/2	1800	145T	EHM9214T	471	LS	11.62	37	85.5	208-230/460	2.1	1
		145T	HM9214T	330	LS	11.62	36	84	208-230/460	2.2	
2	1800	145T	EHM9218T	555	LS	12.13	42	85.5	208-230/460	2.7	1
		145T	HM9218T	357	LS	11.62	39	84	208-230/460	3	
3	1800	182T	EHM9222T	597	LS	15.38	66	87.5	208-230/460	4.2	1
		182T	HM9222T	387	LS	14.00	60	86.5	208-230/460	4.2	
5	1800	184T	EHM9226T	653	LS	16.50	81	88.5	230/460	6.7	1,30
		184T	HM9226T	427	LS	15.00	68	87.5	208-230/460	6.9	
7 1/2	1800	213T	EHM9229T	961	LS	17.45	117	91.7	208-230/460	9.4	1
		213T	HM9229T	595	LS	17.00	95	88.5	208-230/460	10	
10	1800	215T	EHM9232T	1,164	LS	16.32	143	90.2	208-230/460	13.4	1
		215T	HM9232T	746	LS	16.32	117	89.5	208-230/460	13.4	
15	1800	254T	EHM9235T	1,649	LS	20.50	187	91.7	208-230/460	19.2	1
		254T	HM9235T	1,119	LS	19.75	165	91	208-230/460	19	
20	1800	256T	HM9239T	1,362	LS	22.25	235	91.7	230/460	24	30
		284T	HM9242T	1,652	LS	23.44	226	91.7	230/460	30	30
30	1800	286T	EHM9246T	2,763	LS	25.06	339	93	230/460	37	1,30
		286T	HM9246T	1,908	LS	24.94	280	92.4	230/460	36	30
40	1800	324T	HM9249T	2,461	LS	26.19	350	93	230/460	47.5	30
		324T	HM9252T	2,852	LS	27.19	500	93	230/460	60.5	30
50	1800	326T	EHM9252T	3,978	LS	27.19	380	93.6	230/460	62	1,30
		364T	HM9255T	3,521	LS	27.94	523	93.6	230/460	72.5	30
75	1800	365T	HM9258T	4,312	LS	29.94	544	94.1	230/460	88	30
<b>F3 Mounting</b>											
1/2	3600	56	H3M9201	223	LS	10.25	20	68	230/460	1	28,30
		56	EH3M9202	328	K	10.25	24	80	230/460	0.85	28,30
		56	H3M9202	250	LS	10.25	22	74	230/460	1	1,28,30
3/4	3600	56	EH3M9204	329	K	10.88	25	81.5	230/460	1	1,28,30
		56	H3M9204	263	LS	10.25	24	78.5	230/460	1.1	28,30
	1800	56	EH3M9105	412	K	11.97	31	78.5	230/460	1.2	28
		56	H3M9205	277	LS	10.88	27	75.5	208-230/460	1.5	
1	3600	56	EH3M9206	380	K	11.75	29	82.5	230/460	1.25	1,28,30
		56	H3M9206	302	LS	10.88	27	77	208-230/460	1.6	
1 1/2	1800	143T	EH3M9210T	497	LS	11.12	37	84	208-230/460	1.5	1
		3600	H3M9212T	365	LS	11.12	32	82.5	208-230/460	2	
	1800	143T	H3M9214T	333	LS	11.62	39	84	208-230/460	2.2	
		145T	EH3M9214T	517	LS	11.62	39	85.5	208-230/460	2.1	1
2	3600	143T	EH3M9217T	572	LS	11.62	43	85.5	208-230/460	2.5	1
		145T	H3M9217T	403	LS	11.62	41	84	208-230/460	2.6	
	1800	145T	EH3M9218T	555	LS	12.13	45	85.5	208-230/460	2.7	1
		145T	H3M9218T	361	LS	11.62	43	84	208-230/460	3	
3	3600	145T	EH3M9221T	579	LS	13.00	48	85.5	208-230/460	3.7	1
		145T	H3M9221T	428	LS	12.13	45	84	208-230/460	3.7	
	1800	182T	EH3M9222T	597	LS	15.38	64	87.5	208-230/460	4.2	1
		182T	H3M9222T	391	LS	14.00	61	86.5	208-230/460	4.2	

(a) See notes on inside back flap and pages 5-6.

HVAC Variable Torque, Three Phase, ODP

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>F3 Mounting (continued)</b>											
5	3600	182T	EH3M9225T	634	LS	14.63	59	86.5	230/460	6	1,28,30
		182T	H3M9225T	443	LS	14.00	55	85.5	208-230/460	6.1	
	1800	184T	EH3M9226T	653	LS	16.50	78	88.5	230/460	6.7	1,28,30
		184T	H3M9226T	431	LS	15.00	69	87.5	208-230/460	6.9	
7 1/2	3600	184T	EH3M9228T	1,005	LS	15.00	74	89.5	230/460	16.6	1,28,30
		184T	H3M9228T	610	LS	15.00	66	87.5	208-230/460	8.7	
	1800	213T	EH3M9229T	961	LS	17.45	117	91.7	208-230/460	9.4	1
		213T	H3M9229T	601	LS	17.00	104	88.5	208-230/460	10	
10	3600	213T	EH3M9231T	1,145	LS	16.32	116	89.5	208-230/460	12	1
		213T	H3M9231T	765	LS	16.32	107	88.5	208-230/460	11.6	
	1800	215T	EH3M9232T	1,164	LS	16.32	142	90.2	208-230/460	13.4	1
		215T	H3M9232T	753	LS	16.32	110	89.5	208-230/460	13.4	
15	3600	215T	EH3M9233T	1,631	LS	17.45	143	91	230/460	32.4	1,28,30
		215T	H3M9233T	1,118	LS	16.32	125	89.5	208-230/460	17.5	
	1800	254T	EH3M9235T	1,649	LS	20.50	187	91.7	208-230/460	19.2	1
		254T	H3M9235T	1,129	LS	19.75	158	91	208-230/460	19	
20	3600	254T	H3M9238T	1,428	LS	19.75	170	90.2	208-230/460	22	
		256T	EH3M9238T	1,915	LS	21.69	186	91	230/460	23.5	1,28,30
	1800	256T	EH3M9239T	2,072	LS	21.69	242	91.7	230/460	25	1,28,30
		256T	H3M9239T	1,375	LS	22.25	235	91.7	230/460	24	28,30
25	3600	256T	H3M9241T	1,726	LS	21.69	221	91	230/460	29	28,30
		284T	EH3M9242T	2,525	LS	23.81	312	92.4	230/460	32	1,28,30
	1800	284T	H3M9242T	1,668	LS	23.44	252	91.7	230/460	30	28,30
		284TS	EH3M9244T	2,713	LS	23.56	250	91.7	230/460	33	1,28,30
30	3600	284TS	H3M9244T	1,828	LS	22.06	235	91	230/460	35	28,30
		286T	EH3M9246T	2,763	LS	25.06	339	93	230/460	37	1,28,30
	1800	286T	H3M9246T	1,926	LS	24.94	249	92.4	230/460	36	28,30
		286TS	EH3M9248T	3,499	LS	23.56	288	92.4	230/460	45	1,28,30
40	3600	286TS	H3M9248T	2,576	LS	23.56	251	91.7	230/460	46	28,30
		324T	EH3M9249T	3,604	LS	27.19	378	93.6	230/460	48	1,28,30
	1800	324T	H3M9249T	2,484	LS	26.19	339	93	230/460	47.5	28,30
		324T	EH3M9252T	2,879	LS	27.19	378	93	230/460	60.5	28,30
60	1800	364T	H3M9255T	3,554	LS	27.94	475	93.6	230/460	72.5	28,30
75	1800	365T	EH3M9258T	6,151	LS	30.69	553	94.5	230/460	86	1,28,30
		365T	H3M9258T	4,353	LS	29.94	544	94.1	230/460	88	28,30

(a) See notes on inside back flap and pages 5-6.

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

**BALDOR • RELIANCE**

**HVAC  
Variable Torque,  
Three Phase, TEFC**

**1/2 thru 75 Hp**

**NEMA 56 thru 365T**

**Applications:** Heating, ventilation and air conditioning blower and fan motors.



**Features:** Heavy-gauge steel frame construction (1-10 hp), ball bearings, 1.15 service factor. Dynamically balanced rotors for reduced vibration and quiet operation. Suitable for mounting in any position. "HM" models meet EPCt efficiencies. "EHM" models meet NEMA Premium® efficiencies. H3M and EH3M motors use low profile top-mounted conduit box.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>F1 Mounting</b>											
1	1800	56HZ	HM9110T	348	LS	13.22	34	78.5	208-230/460	1.7	
		143T	EHM9110T	564	LS	13.31	35	84	208-230/460	0	1
1 1/2	1800	145T	EHM9114T	588	LS	13.31	43	85.5	208-230/460	2	1
		145T	HM9114T	355	LS	13.31	40	84	208-230/460	2.2	
2	1800	145T	HM9118T	610	LS	14.19	54	85.5	208-230/460	2.7	1
		145T	HM9118T	372	LS	13.31	42	84	208-230/460	2.9	
3	1800	182T	EHM9122T	686	LS	16.79	74	88.5	208-230/460	3.9	1
		182T	HM9122T	440	LS	16.52	67	87.5	208-230/460	4.15	
5	1800	184T	EHM9126T	751	LS	18.29	92	88.5	230/460	6.4	1,30
		184T	HM9126T	503	LS	16.79	75	87.5	230/460	7.1	30
7 1/2	1800	213T	EHM9129T	1,082	LS	19.03	124	91.7	208-230/460	9.4	1
		213T	HM9129T	645	LS	17.91	128	89.5	208-230/460	10.1	1
10	1800	215T	EHM9132T	1,220	LS	19.03	126	90.2	208-230/460	12.8	1
		215T	HM9132T	788	LS	19.03	127	89.5	208-230/460	13.5	1
15	1800	254T	EHM9135T	1,882	LS	23.57	255	91.7	230/460	18.3	1,30
		254T	HM9135T	1,347	LS	21.12	236	91	208-230/460	18.5	1
20	1800	256T	EHM9139T	2,281	LS	23.16	265	91.7	230/460	24	1,30
		256T	HM9139T	1,662	LS	22.82	269	91	230/460	25	1,30
25	1800	284T	EHM9142T	2,986	LS	27.76	403	93	230/460	30	1
		284T	HM9142T	2,063	LS	25.97	416	92.4	230/460	29	1,30
30	1800	286T	EHM9146T	3,546	LS	27.76	353	93	230/460	36	1
		286T	HM9146T	2,398	LS	25.96	322	92.4	230/460	36	1,30
40	1800	324T	EHM9149T	4,635	LS	30.40	579	93.6	230/460	46	1
		324T	HM9149T	3,202	LS	30.39	455	93	230/460	47	1
50	1800	326T	EHM9152T	5,065	LS	30.40	611	93.6	230/460	58	1
		326T	HM9152T	3,340	LS	30.40	566	93	230/460	59	1,30
60	1800	364T	EHM9155T	8,100	LS	32.84	808	94.1	230/460	70	1
		364T	HM9155T	5,002	LS	32.84	753	93.6	230/460	70	1,30
75	1800	365T	HM9158T	6,179	LS	32.84	810	94.1	230/460	86	1,30
<b>F3 Mounting</b>											
1/2	3600	56	EH3M9101	353	K	11.35	21	72	230/460	1	2,28
		56	H3M9101	261	LS	11.35	21	68	230/460	1	28
	1800	56	EH3M9102	345	K	11.35	27	76	230/460	1	28
		56	H3M9102	283	LS	11.35	24	74	230/460	1	28
3/4	3600	56	EH3M9104	386	K	11.35	24	81.5	230/460	1	1,28
		56	H3M9104	288	LS	11.35	24	75.5	230/460	1.2	28
1	1800	56	H3M9105	309	K	11.35	27	75.5	208-230/460	1.5	
		56	EH3M9106	437	LS	11.35	25	77	230/460	1.4	1,28
	3600	56	H3M9106	337	LS	11.35	24	75.5	230/460	1.8	28
		56Z	H3M9110	361	LS	13.22	31	78.5	208-230/460	1.7	
1 1/2	1800	143T	EH3M9110T	564	LS	12.31	34	84	208-230/460	0	1
		143T	EH3M9112T	579	LS	13.31	42	84	208-230/460	1.9	1
	3600	143T	H3M9112T	451	LS	13.31	40	82.5	208-230/460	2.1	
		145T	EH3M9114T	588	LS	13.31	39	85.5	208-230/460	2	1
	1800	145T	H3M9114T	358	LS	13.31	44	84	208-230/460	2.2	

(a) See notes on inside back flap and pages 5-6.

■ Cast Iron Frame

**HVAC Variable Torque, Three Phase, TEFC**

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>F3 Mounting (continued)</b>											
2	3600	145T	<b>EH3M9117T</b>	635	LS	14.19	49	86.5	230/460	2.4	1,28
		145T	<b>H3M9117T</b>	518	LS	13.31	41	84	208-230/460	2.6	
	1800	145T	<b>EH3M9118T</b>	610	LS	14.19	51	85.5	208-230/460	2.7	1
		145T	<b>H3M9118T</b>	375	LS	14.31	45	84	208-230/460	2.9	
3	3600	182T	<b>EH3M9121T</b>	704	LS	15.14	53	86.5	208-230/460	3.6	1
		182T	<b>H3M9121T</b>	547	LS	15.14	68	85.5	208-230/460	3.7	1
	1800	182T	<b>EH3M9122T</b>	686	LS	16.79	75	88.5	208-230/460	3.9	1
		182T	<b>H3M9122T</b>	444	LS	16.52	68	87.5	208-230/460	4.1	
5	3600	184T	<b>EH3M9125T</b>	778	LS	16.79	77	88.5	208-230/460	5.6	1
		184T	<b>H3M9125T</b>	629	LS	16.79	75	87.5	208-230/460	5.8	1
	1800	184T	<b>EH3M9126T</b>	751	LS	18.29	92	88.5	230/460	6.4	1,28
		184T	<b>H3M9126T</b>	508	LS	16.79	78	87.5	230/460	7.1	28
7 1/2	3600	213T	<b>EH3M9128T</b>	1,169	LS	17.91	120	89.5	208-230/460	8.6	1
		213T	<b>H3M9128T</b>	926	LS	18.55	100	88.5	208-230/460	8.7	1
	1800	213T	<b>EH3M9129T</b>	1,082	LS	19.03	113	91.7	208-230/460	9.4	1
		213T	<b>H3M9129T</b>	651	LS	17.91	116	89.5	208-230/460	10.1	1
10	3600	215T	<b>EH3M9131T</b>	1,185	LS	19.03	140	90.2	230/460	11.5	1,28
		215T	<b>H3M9131T</b>	971	LS	17.91	125	89.5	208-230/460	11.5	1
	1800	215T	<b>EH3M9132T</b>	1,220	LS	19.03	137	90.2	208-230/460	12.8	1
		215T	<b>H3M9132T</b>	795	LS	19.03	128	89.5	208-230/460	13.5	1
15	3600	254T	<b>H3M9133T</b>	1,538	LS	21.57	158	90.2	208-230/460	17	1
	1800	254T	<b>EH3M9135T</b>	1,882	LS	23.57	242	91.7	230/460	18.3	1,28
		254T	<b>H3M9135T</b>	1,359	LS	22.07	187	91	208-230/460	19.4	
20	1800	256T	<b>EH3M9139T</b>	2,281	LS	23.57	248	91.7	230/460	23	1,28
		256T	<b>H3M9139T</b>	1,678	LS	23.57	250	91	230/460	24	1,28

(a) See notes on inside back flap and pages 5-6.

■ Cast Iron Frame

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors