

General Purpose Single Phase Open Dripproof (ODP), C-Face Footed, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment.

FEATURES:

- Double Shielded Ball Bearings
- Rigid Base
- Class B Insulation
- Continuous Duty
- 40°C Ambient
- F1 Assembly
- Reversible Rotation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/208-230	56C	6185	\$227	DS-3FMP	1.35	9.9	16	6.2/3.1	24, LA
1/3	1800	115/230	56C	D13C2PC	\$273	DS-3FMP	1.35	10.1	19	7.6/3.8	25, LA
	1800	115/208-230	56C	D13C2JC	\$273	DS-3F	1.35	11.0	19	8.8/4.0-4.4	25
1/2	3600	115/208-230	56C	D12C1JC	\$160	DS-3FMP	1.25	11.0	21	9.2/4.4-4.6	25
	1800	115/230	56C	D12C2PC	\$292	DS-3F	1.25	10.0	22	9.0/4.5	25, LA
	1800	115/208-230	56C	D12C2JC	\$292	DS-3F	1.25	11.0	22	9.0/4.3-4.5	25
3/4	3600	115/208-230	56C	D34C1JC	\$205	DS-3FMP	1.25	11.4	23	10.4/5.3-5.2	25
	1800	115/230	56C	D34C2PC	\$356	DS-3FMP	1.25	10.8	26	12.4/6.2	25, LA
	1800	115/208-230	56C	D34C2JC	\$356	DS-3F	1.25	11.0	26	11.4/5.7-5.7	25
1	3600	115/208-230	56C	D1C1JC	\$240	DS-3FMP	1.25	11.4	28	14.6/6.9-7.3	25
	1800	115/208-230	143TC	D1C2J14C	\$409	DS-3F	1.25	11.9	40	14.8/7.5-7.3	25
	1800	115/208-230	56HC	D1C2JHC	\$409	DS-3F	1.25	12.0	20	14.8/7.5-7.3	25
1-1/2	3600	115/208-230	143TC	D32C1J14C	\$295	DS-3FMP	1.15	11.9	32	18.6/9.8-9.3	25
	3600	115/208/230	56HC	D32C1JHC	\$295	DS-3FMP	1.15	11.9	32	18.6/9.8-9.3	25
	1800	115/230	145TC	6180	\$431	DS-3FMP	1.15	12.8	43	20.4/10.2	25, LA
	1800	115/208-230	145TC	D32C2J14C	\$431	DS-3F	1.15	13.0	43	19.2/10.0-9.6	25
	1800	115/208-230	56HC	D32C2JHC	\$430	DS-3F	1.15	12.9	37	19.2/10.0-9.6	25
2	3600	115/208-230	145TC	D2C1J14C	\$380	DS-3FMP	1.15	12.4	35	22.4/12.4-11.2	25
	3600	115/208-230	56HC	D2C1JHC	\$380	DS-3FMP	1.15	12.9	35	22.4/12.4-11.2	25
	1800	115/208-230	145TC	D2C2J14C	\$504	DS-3F	1.15	13.0	42	20.0/11.3-10.0	25
	1800	115/230	182TC	D2C2P18C	\$588	DS-3SP	1.15	15.8	72	23.2/11.6	18
	1800	115/208-230	56HC	D2C2JHC	\$503	DS-3F	1.15	13.0	41	20.0/11.3-10.0	25
3	3600	115/230	182TC	D3C1P18C	\$718	DS-3SP	1.15	17.9	83	16.0/32.0	18
	3600	208-230	56HC	D3CA1JHC	\$455	DS-3FMP	1.15	14.0	41	16.3-14.7	24
	1800	115/230	184TC	D3C2P18C	\$723	DS-3SP	1.15	15.8	68	38.0/19.0	18
5	3600	230	184TC	D5C1K18C	\$801	DS-3SP	1.15	17.9	84	19.6	18
	1800	230	184TC	D5C2K18C	\$898	DS-3SP	1.15	17.9	88	22.0	18
	1800	230	213TC	D5C2K21C	\$959	DS-3SP	1.15	19.4	100	22.0	25
7-1/2	3600	230	213TC	D7C1K21C	\$1,352	DS-3PO	1.15	19.4	136	30.4	25
	1800	230	215TC	D7C2K21C	\$1,098	DS-3SP	1.15	20.9	105	35.6	25
10	3600	230	215TC	D10C1K21C	\$1,555	DS-3SP	1.15	20.9	168	40.0	25
	1800	230	215TC	D10C2K21C	\$1,233	DS-3SP	1.15	20.9	110	42.2	25

Note 18 Incorporates Run Capacitor
 Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-protected
 Note LA Limited Availability