

Model: 155M

Cast Iron Flanged End Basket Strainers, Clamped Cover Sizes: 2" - 16"(50 - 400mm)

Pressure/Temperature Non-Shock		
Model	Material	Rating
155M 2" - 12"	Cast iron	200psi @ -20 to 150°F 13.79 bar @ 65.56°C 125psi @ 450°F 8.62 bar @ 232.22°C
155M 14" - 16"	Cast iron	150psi @ -20 to 150°F 10.34 bar @ 65.56°C 100psi @ 353°F 6.89 bar @ 178.33°C

Max. temp. can be limited by O-ring material. Consult Factory. All units with knob closures are rated 200psi.

155M

Class 125



Model 155M

Strainers provide economical protection for costly pumps, meters, valves, and other similar mechanical equipment by straining foreign matter from the connected piping system. Installation of a strainer before mechanical equipment can ensure trouble free service and avoid costly shutdowns for repair or replacement of equipment damaged by foreign matter. The size of the perforation or mesh in the basket screen will determine the smallest particles captured. See Strainer Information section in the Mueller Steam Specialty Engineering binder for detailed information including sizes and materials available.

Typical Service

- These are well-suited for high flow applications such as swimming pool installations.
- They are especially suited for medium or coarse straining. For finer straining, see Model 125.

Features

- The angular cutaway design of the baskets allows a straight through flow, resulting in extremely low pressure drop. See Technical Data section of Mueller Steam Specialty Engineering binder for Pressure Drop Charts.
- Tapped and plugged NPT drain on the strainer bottom at location D. See next page.

Construction

- Cover is secured with quick-opening knobs to minimize service time.

Capacity

- Minimum 6 to 1 ratio

Galvanizing

- Available on all sizes, consult factory

Baskets

MODEL	SIZES	LIQUID	
		MATERIAL	OPENING
155M	2" - 4"	304SS	.045 perf
155M	5" and Up	Consult Factory	

Materials

	155M
Body	Cast Iron ASTM A126-B
Cover	A516-70 Plate
O-Ring	Buna-N


Pressure Drop

See Pressure Drop Charts in the Technical Data section of the Mueller Steam Specialty Engineering binder.

Dimensions and Weights

SIZE	DIMENSIONS								WEIGHT		
	A		B		C		D (NPT)		E SCREEN REMOVAL		
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
2	50	8 ⁵ / ₈	219	5 ⁷ / ₈	149	5 ³ / ₄	146	1 ¹ / ₂	15	10 ¹ / ₈	276
2 ¹ / ₂	65	7 ⁹ / ₁₆	189	5 ³ / ₈	137	5 ¹ / ₄	133	3 ¹ / ₄	20	9	229
3	80	8 ³ / ₄	222	5 ¹ / ₄	133	6 ¹ / ₈	168	3 ¹ / ₄	20	11 ¹ / ₄	286
4	100	11 ³ / ₁₆	284	8	203	7 ⁷ / ₈	187	1	25	15 ¹ / ₂	394
5	125	12 ¹ / ₄	311	10 ¹ / ₄	260	6 ⁹ / ₁₆	167	1	25	14 ¹ / ₄	386
6	150	14	356	10 ³ / ₈	270	8 ⁷ / ₈	225	1 ¹ / ₄	32	18 ¹ / ₄	464
8	200	17 ¹ / ₈	435	15 ¹ / ₈	384	10	254	1 ¹ / ₂	40	23 ³ / ₈	594
10	250	22	559	16	406	12 ³ / ₈	321	1 ¹ / ₂	40	29	737
12	300	25 ¹ / ₄	645	23 ¹ / ₁₆	602	14	356	2	50	37 ¹ / ₂	953
14	350	29 ¹ / ₄	756	26 ³ / ₄	679	17 ¹ / ₂	445	—	—	42	1066
16	400	31 ¹ / ₈	810	29 ¹ / ₂	749	19	483	—	—	50	1270
										1040	472

Consult Factory for Larger sizes.



Model 155M

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A Division of Watts Water Technologies, Inc.

USA: 1491 NC Hwy 20 West St. Pauls, NC 28384; www.muellersteam.com

Tel: 910-865-8241 Fax: 910-865-6220

Toll Free Phone 1-800-334-6259 Toll Free Fax: 1-800-421-6772