

Type 1570 Emergency Power Supply Unit



For valve types:
423, 428

*For panel mounting or
direct attachment*

Voltage: 24 V d.c.
Permissible voltage variation: ± 10%
Power consumption: 2 W
N.B.: A charging period of at least 16 hrs is required before putting the unit into service
Max. input/output loading: 24 V d.c., 4 A
Output voltage: U₀16.5 V d.c.
Capacity: 110 mA/h
Internal fuse: M 4 /250 V
Weight: .90 lbs
Cable gland: PG 13.5

Type 1572 Voltage Transformer



For valve types:
423, 428

*For panel mounting or
direct attachment*

Voltage: 110, 220 V/50-60 Hz
Permissible voltage deviation: ± 10%
Power consumption: 35 VA
Output voltage: 20 V d.c. unsmoothed
Output current: 1.4 A
Input fusing: M 1.6/250 V
Weight: 2.14 lbs
Cable gland: PG 13.5

Type 1275 Digital Display Unit



For accessory types:
901, 1270, - 1273, 3020,
3120, 3220

For panel mounting (DIN)

Type 1279 Digital Display Unit *for % indication*



For accessory types:
901, 1270/127, 3020, 3120, 3220

Euro-card for 19" or 24" racks
with 31 pole terminal strip
complying with DIN 41617

Type 3000 Accumulated flow counter *with and without batch controller*



For accessory types:
901, 1270, - 1273, 3020, 3120, 3220

For panel mounting (DIN)