

Automatic Vertical Screen (AVS)

The Automatic Vertical Screen (AVS) offers the unique ability to recess the screen case into the floor for a decorative enclosure



Automatic Vertical Screen (AVS)

The Automatic Vertical Screen offers the unique ability to recess the screen case into the floor for a decorative enclosure. A specially designed scissor system raises the screen to its fullest extension. The unique trap door system opens prior to the screen's ascent, and closes after the screen descends. The AVS is available in front projection models only.

The AVS is available with a variety of Stewart's front projection materials. Our exclusive Tab-Guy™ tensioning system ensures a smooth and completely flat screen surface. Matte black overscan borders provides a perfectly masked image area. Microperf X2 option is available when acoustic transparency is required.

SPECIFICATIONS:

SPECIFICATIONS:	
Electronically controlled screen	Included
system with trapdoor	
Aluminum & Sintra housing/case	Included
3-1/4" roller tube with insulated drive	Included
Tab-Guy™ tensioning system	Included
Matte black over-scan border*	Included
SCREEN MATERIAL:	
Front projection	Included
PERFORATIONS:	
Microperf X2 THX Ultra	Optional
Cinemaperf	Optional
MOUNTING:	
Floor mount	Included
SCREEN MOTOR:	
120 Volt	Included
220 Volt	Optional
SCREEN CONTROL:	
HVS (3-position high voltage wall switch	h) Included
LVC (low voltage control)	Included
includes 3-button switch)	
STI (12V screen trigger interface)	Optional
IRR (IR remote)	Optional
CASE/HOUSING DIMENSIONS:	
Case height	10.25" (260mm)
Case depth	15.25" (387mm)

Stewart Filmscreen is synonymous for superior quality, custom craftsmanship and long, trouble-free product life. As every Stewart product is handcrafted, custom sizes & configurations are easily accommodated. Contact your local Stewart Representative today and let us build one for you!



FEATURES:

- · Electronically controlled vertical rising screen system with trapdoor
- · Custom roller tube with sound-dampening insulated screen drive
- Aluminum & Sintra housing/case (standard black finish)
- Available with a variety of Stewart's front projection materials
- Exclusive Tab-Guy[™] tensioning system ensures a smooth & flat screen surface
- Matte black-over scan border* provides a perfectly masked image area
- · Recess within floor or custom cabinetry
- Standard 3-button low voltage wall switch (LVC) included
- Optional control systems offered
- · Custom sizes & aspect ratios available
- AllRise is available when larger size or rear projection is required



HDTV Format 1.78:1/16:9

Model	lmage	Image	Image	Batten	Unit
	Diagonal	Height	Width	Length	Weight
VS082H	82	40.5	72	84	90
	(2083)	(1029)	(1829)	(2134)	(41)
VS092H	92	45	80	92	95
	(2337)	(1143)	(2032)	(2337)	(43)
VS100H	100	49	87	99	110
	(2540)	(1245)	(2210)	(2515)	(50)
VS110H	110	54	96	108	115
	(2794)	(1372)	(2438)	(2743)	(52)
VS123H	123	60	107	108	125
	(1524)	(2718)	(2438)	(2743)	(56)

NTSC Format 1.33:1/4:3

Model	Image	Image	lmage	Batten	Unit
	Diagonal	Height	Width	Length	Weight
VS084V	84	50	67	79	90
	(2134)	(1270)	(1702)	(2007)	(41)
VS090V	90	54	72	84	100
	(2286)	(1372)	(1829)	(2134)	(45)
VS100V	100	60	80	92	110
	(2540)	(1524)	(2032)	(2337)	(50)
VS120V	120	72	96	108	120
	(3048)	(1829)	(2438)	(2743)	(54)
VS150V	150	90	120	132	130
	(3810)	(2286)	(3048)	(3353)	(59)

Specifications are subject to change at anytime without notice.

Dimensions above include 4" black drop - over scan border may vary by size.

*CRITICAL: It is extremely important to add only the amount of black drop needed on any Stewart retractable screen model to ensure a smooth and flat image.

Find your local representative at www.stewartfilmscreen.com/reps