

Allianz VT650

Product Standard Features

Allianz VT650 Standard Features :

- Sealed Auxiliary Engine Compartment
- Coolant/Oil Pressure Shutdown System
- Variable Speed Throttle Switch
- 51 gal (190 L) Shared Fuel Tank
- 8.5 cu yd Hopper (6.4 cu meter) (Volumetric)
- All Chromium Stainless Steel Body
- 54 degree Dump Angle
- 2 Hopper Drain Hoses on Rear Door
- Twin, side mounted Hopper Access Doors
- 343 gal (1250 L) Chromium Stainless Steel Water Tank
- Front & Side Gutter Broom Water Spray Jets
- Widesweep Water Spray Jets
- Dual Widesweep Regulators
- Remote Widesweep Greaser
- Vacuum Nozzle Water Spray Jets (2 per)
- Dual Beacons with Limb Guards
- Gutter Broom Work lights
- IP67 External electrical Connectors
- L.E.D.'s on all Solenoid Plugs
- Gear Box Driven Vacuum Blower
- 10 in. (254 mm) dia Vacuum Hose
- Maxigap Nozzle Tilt System
- 16" x 50" (406 mm x 1275 mm) wide sweep Broom
- 28 in. (711 mm) dia. Gutter Brooms
- Steel Gutter Broom Segments
- 96 in. (2425 mm) Wide Sweeping Path
- Powder Coated Sweep Gear
- 20 gal (75 L) Hydraulic Oil Tank
- Backup Alarm
- 125 micron Suction Hydraulic Filtration
- Remote Oil Drain
- Turbo III Precleaner - Auxiliary Engine
- 25' (7.6 m) Hydrant Hose with Coupling
- Weatherproof Systems Locker
- 25 ft (7.6 m) Washdown Hose
- Convex mirrors and Brackets



Allianz Sweeper

4651 Schaefer Avenue, Chino
CA 91710, USA

Tel : 1 (909) 613-5600

Fax : 1 (909) 613-5736

E-Mail : info@allianzmadvac.com

Web : www.allianzsweeper.com

