

Shelving Selection Guide



	Automotive	Industrial	Galvanized	Painted Wire	Chrome	Toolroom	Rivet	Commercial
APPLICATION	Quick adjustment for changing inventories.	All-purpose standard and heavy-duty storage.	High humidity, unheated storage; storage of solvents, oily or greasy parts.	Light industrial; for cleanliness and sprinkler access.	Commercial or Industrial; for cleanliness and sprinkler access.	Heavy-duty storage of tool-room supplies.	Light industrial, record storage, commercial.	Commercial office, light industrial. Individual, stand alone sections.
SHELF CONSTRUCTION	20 ga. flanged	18, 20, 22 ga. box, 18 ga. flanged, lapped and welded.	18 ga. flanged, corners lapped and welded	Channel frame w/ 1/2", 3/4" wire ribbing.	Wire-over-wire waterfall construction.	18 ga. flanged, corners lapped and welded	Particle board with 14-ga. steel beams.	Dbl.-flanged at front and rear; corners lapped and welded.
UPRIGHT CONSTRUCTION	Flanged and ribbed	T-Post, B.P., O.A., 16 ga. cold rolled, formed steel. Double thick.	T-Post 16 ga. cold-rolled formed steel. Double thick.	T-Post 16 ga. cold-rolled formed steel. Double thick.	Round, digital post.	T-Post 16 ga. cold-rolled formed steel. Double thick.	14-ga. steel, angle or T-post	Offset Angle or offset
ADJUSTABILITY	1 1/2" centers	1 1/2" centers	1 1/2" centers	1 1/2" centers	1" centers	1 1/2" centers	1 1/2" centers	Offset 1 1/2" centers
AVAILABLE WIDTHS	37 3/8"	36", 42", 48"	36"	36", 48"	48", 60", 72"	36"	12"-96" in 12" increments. 69" R.S.	Offset 36, 42, 48
AVAILABLE DEPTHS	12 3/8"	12", 18", 24"	12", 18", 24"	18", 24"	18", 24"	12", 18", 24"	12", 24" - 48", in 6" increments.	18" 24"
AVAILABLE HEIGHTS	84"	84", 96", 120"	84", 96", 120"	84", 96", 120"	62", 74", 86"	84", 96", 120"	60", 72", 84", 96", 120"	Offset 84", 96", 120"
TYPICAL CAPACITIES	200 lbs.	600-1300 lbs	700-800 lbs.	400 to 600 lbs.	600-1200 lbs.	700-800 lbs.	600-1200 lbs.	600 lbs.
Stock Colors	Dove Gray, Putty	Dove Gray, Putty, Wedgewood Blue	Shelves: Galvanized, Uprights: Gray, Putty, Blue	Dove Gray	Super Bright Plating Plus Chrome	Dove Gray	Putty	Dove Gray, Putty

Shelf Load Capacities for 8000 Series Shelving

Size W x D Inches	22-Ga. Medium Box "W"		20-Ga. Heavy Duty Box "W"		18-Ga. Extra Heavy Duty Box "W"		18-Ga. Traditional Flanged	
	Cat. No.	Cap.	Cat. No.	Cap.	Cat. No.	Cap.	Cat. No.	Cap.
30 x 30	N/A	N/A	8593H	800	N/A	N/A	N/A	N/A
36 x 12	8560M	600	8560H	800	8560X	1150	8560	700
36 x 15	8584M	600	8584H	825	8584X	1200	8584	725
36 x 18	8561M	600	8561H	900	8561X	1300	8561	750
36 x 24	8562M	600	8562H	800	8562X	1150	8562	800
36 x 30	**	**	8585H	740	8585X	950	8585	650
36 x 36	**	**	8586H	640	8586X	850	8586	600
42 x 12	**	**	8565H	650	8565X	830	8565	500
42 x 15	**	**	8587H	650	8587X	880	8587	475
42 x 18	**	**	8566H	720	8566X	900	8566	450
42 x 24	**	**	8567H	700	8567X	880	8567	500
42 x 30	**	**	8588H	650	8588X	850	8588	400
42 x 36	**	**	8589H	625	8589X	820	8589	325
48 x 12	**	**	8300H	600	8300X	750	8300	350
48 x 15	**	**	8590H	600	8590X	700	8590	325
48 x 18	**	**	8301H	600	8301X	700	8301	300
48 x 24	**	**	8302H	560	8302X	750	8302	300
48 x 30	**	**	8591H	540	8591X	730	8591	300
48 x 36	**	**	8592H	480	8592X	640	8592	300

**Please consult your factory representative, Lyon does not generally recommend 22-gauge on industrial shelving requirements larger than 36" x 24"