

7000BT

Eye/Face Washes



FEATURES & BENEFITS

Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

Flow Control

Omni-Flo wrap-around eye/face wash assembly with built-in 6.25 gpm self-regulating flow control offers a superior coverage area and assures efficient water flow.

Valve

Valve is designed to make the flushing of fluid occur with the push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with pre-assembled 16 gauge Type 304 Stainless Steel wall bracket to assist with the installation process.

Protection

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable. Yellow plastic dust cover protects the Omni-Flo eye/face wash from debris further optimizing operation.



SPECIFICATIONS

Model 7000BT wall-mounted eye/face wash shall include wrap around eye/face wash with integral yellow plastic dust cover, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, chrome-plated brass in-line 50 x 50 mesh water strainer, and foam filter. Unit shall also include 16 gauge Type 304 Stainless Steel wall bracket, chrome plated trap, universal sign, 1/2" IPS inlet, and 1-1/2" IPS outlet.

OPTIONS

- Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- Foot Treadle: Model SP220W wall mounted foot control assembly, including powder-coated aluminum treadle and wall bracket for hands free activation of eyewash.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" flow switch when emergency eye/face wash is in use.

To see all options for this model, visit www.hawsc.com.

APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes and face must be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7000BT is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



7260BT-7270BT

AXION MSR™ Eye/Face Wash



FEATURES & BENEFITS

Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

Antimicrobially Treated

AXION MSR™ eye/face wash heads are antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the heads against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face wash product on the market to feature antimicrobial protection.

Strainer

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable.

Bowl

The 11" round green ABS plastic receptor is resistant to damage from alkalies, salt solutions, oils and most acids.

Trap

1-1/4" chrome-plated brass trap with tailpiece allow for the emergency equipment to meet desired requirements for wall mounting.

Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with pre-assembled cast-aluminum wall bracket to assist in the installation process.



OPTIONS

- ❑ Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat# 5,350,112).
- ❑ AXION MSR™ Eyewash: Part Number 0002953155 AXION MSR™ eyewash head option is used to convert the eye/face wash to an eyewash, and is supplied with a 1.3 gpm flow control (part # 0002475339).
- ❑ Tempered Water Blending Systems: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ❑ Tempered Water Blending Systems: Model 9201EF is a thermostatic mixing valve that mixes hot and cold water to supply tempered water to fixtures requiring flow up to 7 gpm @ 30 psi ΔP, sufficient for a single eye-eye/face wash. The unit employs a thermostatic mixing element and includes an outlet temperature gauge.

To see all options for this model, visit www.hawesco.com.

SPECIFICATIONS

Model 7260BT-7270BT wall mounted eye/face wash shall include a green ABS plastic 11" bowl, an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, tail piece and trap and chrome-plated brass in-line 50 x 50 mesh water strainer. Unit shall also include cast-aluminum chromate protected wall bracket, yellow plastic pop-off dust cover for eyewash head, universal sign, 1/2" IPS inlet, and 1-1/2" IPS waste.

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes must be provided within the work area for immediate emergency use. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7260BT-7270BT is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



7261-7271

AXION MSR™ Eye/Face Wash



FEATURES & BENEFITS

Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

Antimicrobially Treated

AXION MSR™ eye/face wash heads are antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the heads against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face wash product on the market to feature antimicrobial protection.

Construction

1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange provide corrosion resistance in a long lasting product.

Strainer

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable.

Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind.

Valve

Valve is designed to make the flushing of fluid occur with the push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

Bowl

The 11" round green ABS plastic receptor is resistant to damage from alkalis, salt solutions, oils and most acids.



SPECIFICATIONS

Model 7261-7271 pedestal eye/face wash shall include a green ABS plastic 11" bowl, an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, and chrome-plated brass in-line 50 x 50 mesh water strainer. Unit shall also include 1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange, yellow plastic pop-off dust cover for eyewash head, universal sign, 1/2" IPS inlet, and 1-1/4" IPS waste.

OPTIONS

- Model 8901RFK, body spray unit with AXION MSR™ eye/face wash head, stay open squeeze lever valve, 8-foot hose, and installation kit.
- Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Patent No. 5,350,112).
- AXION MSR™ Eyewash: Part Number 0002953155 AXION MSR™ eyewash head option is used to convert the eye/face wash to an eyewash, and is supplied with a 1.3 gpm flow control (part # 0002475339).
- Tempered Water Blending Systems: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.

To see all options for this model, visit www.hawasco.com.

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes must be provided within the work area for immediate emergency use. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7261-7271 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



7324

AXION MSR™ Eye/Face Wash



FEATURES & BENEFITS

Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

Antimicrobially Treated

AXION MSR™ eye/face wash heads are antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the heads against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face wash product on the market to feature antimicrobial protection.

Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with green molded ABS plastic wall bracket to assist in the installation process.



OPTIONS

- ❑ Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat# 5,350,112).
- ❑ Tempered Water Blending Systems: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ❑ Tempered Water Blending Systems: Model 9201EF is a thermostatic mixing valve that mixes hot and cold water to supply tempered water to fixtures requiring flow up to 7 gpm @ 30 psi ΔP, sufficient for a single eye-eye/face wash. The unit employs a thermostatic mixing element and includes an outlet temperature gauge.
- ❑ AXION MSR™ Eyewash: Part Number 0002953155 AXION MSR™ eyewash head option is used to convert the eye/face wash to an eyewash, and is supplied with a 1.3 gpm flow control (part # 0002475339).

To see all options for this model, visit www.hawasco.com.

SPECIFICATIONS

Model 7324 wall mounted eye/face wash shall include an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control. Unit shall also include a chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, green molded ABS plastic wall bracket, universal sign, and 1/2" inlet. Note: Floor drain is recommended for this unit.

APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face must be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7324 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



7360BT-7460BT

AXION MSR™ Eye/Face Wash



FEATURES & BENEFITS

Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

Antimicrobially Treated

AXION MSR™ eye/face wash heads are antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the heads against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face wash product on the market to feature antimicrobial protection.

Strainer

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable.

Bowl

The 11" round stainless steel receptor is supplied with a No. 2L bright finish on its exterior, and a satin finish inside.

Trap

1-1/4" chrome-plated brass trap with tailpiece allow for the emergency equipment to meet desired requirements for wall mounting.

Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with pre-assembled cast-aluminum wall bracket to assist in the installation process.



SPECIFICATIONS

Model 7360BT-7460BT wall mounted eye/face wash shall include a stainless steel 11" round bowl, an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, and chrome-plated brass in-line 50 x 50 mesh water strainer. Unit shall also include cast-aluminum chromate protected wall bracket, yellow plastic pop-off dust cover for eyewash head, tailpiece and trap, universal sign, 1/2" IPS inlet, and 1-1/2" IPS waste.

OPTIONS

- ❑ Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat# 5,350,112).
- ❑ AXION MSR™ Eyewash: Part Number 0002953155 AXION MSR™ eyewash head option is used to convert the eye/face wash to an eyewash, and is supplied with a 1.3 gpm flow control (part # 0002475339).
- ❑ Tempered Water Blending Systems: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ❑ Tempered Water Blending Systems: Model 9201EF is a thermostatic mixing valve that mixes hot and cold water to supply tempered water to fixtures requiring flow up to 7 gpm @ 30 psi ΔP, sufficient for a single eye-eye/face wash. The unit employs a thermostatic mixing element and includes an outlet temperature gauge.

To see all options for this model, visit www.hawesco.com.

APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face must be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7360BT-7460BT is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



7361-7461

AXION MSR™ Eye/Face Wash



FEATURES & BENEFITS

Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

Antimicrobially Treated

AXION MSR™ eye/face wash heads are antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the heads against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face wash product on the market to feature antimicrobial protection.

Construction

1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange provide corrosion resistance in a long lasting product.

Strainer

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable.

Quality Control

Eyewash (eye/face wash) and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind.

Valve

Valve is designed to make the flushing of fluid occur with the push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

Bowl

The 11" round stainless steel receptor is supplied with a No. 2L bright finish on its exterior, and a satin finish inside.



SPECIFICATIONS

Model 7361-7461 pedestal eye/face wash shall include a stainless steel 11" round bowl, an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, and chrome-plated brass in-line 50 x 50 mesh water strainer. Unit shall also include 1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange, yellow plastic pop-off dust cover for eyewash head, universal sign, 1/2" IPS inlet, and 1-1/4" IPS waste.

OPTIONS

- ❑ Model 8901RFK, body spray unit with AXION MSR™ eye/face wash head, stay open squeeze lever valve, 8-foot hose, and installation kit.
- ❑ Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat# 5,350,112).
- ❑ AXION MSR™ Eyewash: Part Number 0002953155 AXION MSR™ eyewash head option is used to convert the eye/face wash to an eyewash, and is supplied with a 1.3 gpm flow control (part # 0002475339).
- ❑ Tempered Water Blending Systems: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.

To see all options for this model, visit www.hawsco.com.

APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes and face must be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7361-7461 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

