

FOR SPILL CONTROL

Large-diameter Funnels provide a simple cost-effective way to collect liquids and keep drum tops clean.

Environmental Products Gator® Polyethylene Spill Control Funnels fit all closed head 30- and 55-gallon (110L & 200L) drums. Low-profile, wide-diameter opening offers large "target" for quick, easy pouring. Scalloped, sloping design minimizes splash and prevents containers from resting in their own liquids. Large flat well at the throat of funnel allows for passive draining of paint cans, filters, buckets and other containers. Molded-in hook makes a convenient way to store optional funnel cover.

Funnel for Flammables includes a drum fill vent with 6" (152mm) perforated brass flame arrester. Threaded bung cap seals in flammable vapors under normal storage conditions. In high temperatures, a pressure relief valve opens to protect drum and prevent explosion. Flame arrester prevents fire flashback. It also offers vacuum relief by allowing hot contents to cool, protecting against drum collapse.

Gator® Spill Control Funnels

Product Description	Sump Cap. Gallons	Outside Dia x H (mm)	Compliance	Model No.
Funnel for nonflammables	2 ¹ / ₂ /9L	21" x 3 ¹ / ₄ "(533 x 83)	OSHA	28210
Funnel for flammables	21/2/9L	21" x 3 ¹ / ₄ "(533 x 83)	OSHA	28211
Cover for funnel 28210	-	19" x 1 ¹ / ₄ "(482 x 32)	-	28215

Product	Sump Cap.	Outside					
Description	Gallons	Dia x H (mm)	Compliance	Model No.			
Funnel for nonflammables	21/2/9L	21" x 3 ¹ / ₄ "(533 x 83)	OSHA	28210			
Funnel for flammables	21/2/9L	21" x 3 ¹ / ₄ "(533 x 83)	OSHA	28211			
Cover for funnel 28210	-	19" x 1 ¹ / ₄ "(482 x 32)	-	28215			
See page 113 for other steel safety funnels							

Safely manage hazardous drums.

All-weather, chemical-resistant Gator-Tuff polyethylene drum collection centers stand up to the harshest environments. All are designed to be forkliftable for easy relocation.

The Single-Drum Collection Center has a large diameter opening at the top for easy loading. It is ideal for storing, pumping or collecting liquids, and its compact size makes it the perfect choice when space is limited. Empty bases nest for convenient storage. Steel Dolly accessory is available for easy collection center relocation.

The Double-Drum Collection Center accommodates two 55-gallon (200L) drums, and is ready to contain any accidental spills. Dual covers can be opened separately to provide convenient access to either drum, or they can be closed together and locked to prevent unauthorized access (lock included). The base can be used as an indoor pumping station. Both collection centers are fully compliant; each unit's sump capacity meets EPA requirements.

The 95-gallon Overpack Salvage Drum is the safe and economical solution for the transportation and temporary storage of damaged or leaking drums of hazardous materials. Rugged, UV-protected polyethylene withstands the rigors of land, air, and sea transportation. "X" rating offers the highest UN and D.O.T. certification available - can be used with all packing classes of hazardous materials I, II, and III including solvents, acids, poisons and explosives. Perfect for emergency response, contamination site cleanup, and spill control kits. Twist-on threaded lid makes closure safe and easy with no separate, troublesome metal band needed. Units nest when empty for compact storage.

Gator® Collection Centers and Overpack

Product Description	Sump Cap. Gallons	Outside Dim. W x D x H (mm)	Compliance	Model No.
Double-drum collection center	180/681L	60" x 39" x 47"(1524 x 991 x 1194)	EPA,U	28250
Collection center - base only	180/681L	60" x 39" x 27"(1524 x 991 x 686)	EPA,U	28255
Single-drum collection center	66/250L	33" top dia x 313/4"(838 x 806)	EPA,U	28268
Steel drum dolly	_	fits 28268	-	28270
Overpack salvage drum	95/360L	31" x 43 ¹ / ₄ "(787 x 1099)	D.O.TUN	28201

Overpack #28201:

UN Marking: 1H2/X340/S. Complies with DOT 49 CFR 173.3(c)(1). Also certified to International Maritime Organization (IMO), International Civil Aviation Organization (ICAO), and International Air Transport Association(IATA).

28201

28250

*See page 8 for Regulation Key.



28268 on

28270 Steel Dolly