



## PROTECTIVE CAP/WELDING HELMET COMBINATIONS

5000 ADJUSTABLE SPEEDY® MOUNTING LOOP SYSTEM for frequent on/off use with protective caps. Welding helmets, faceshields, goggles, etc. may be mounted while the cap is on the head. No tools or modified caps required. (Does not affect ANSI rating.)

PART #	DESCRIPTION
4906GY	Tigerhood lift front with QUICK-LOKS®
5906GY	Tigerhood lift front with 5000 SPEEDY® Loop
52090BK	Futura 4" x 5" with 5000 SPEEDY® Loop



## HIGH PERFORMANCE® FACESHIELD

Four inch faceshield crown is molded from same material as welding helmets for extended service life. Exclusive Channel Grip Mounting System consists of a deep, recessed mounting channel with a wide rim to keep debris away from the crown/window seal. Locking cams hold the faceshield window securely in place. Uses wide, wraparound 16 inch windows to provide 40% more protective area than standard 12 inch windows. Also accepts Extended View 19 inch windows. Available with 3 cap mounting devices including Speedy Loop, Quick-Lok and Quick-Lok Mounting blades for slotted caps.

PART #	DESCRIPTION
F4400	F400 with QUICK-LOK® cups for E2QRW & P2QWR caps
F5400	F400 with 5000 speedy loop
F6400	F400 with slotted cap blades



## CAP PEAK MOUNTED FACESHIELDS

Fully dielectric-mounting bracket provides a positive seal to keep debris from filtering between cap and shield. The shield may be pivoted above the cap between uses without removing the cap. Designed to fit on the front peak of our E-2 and P-2 caps.

PART #	DESCRIPTION
FM70	Faceshield Cap bracket. Fits on the front peak of the E-2 and P-2 caps.
FM71	Faceshield Cap bracket. Fits on full brim protective hats



## FACESHIELD WINDOWS

Lightweight, dimensionally stable, crystal clear, distortion free, impact and scratch resistant windows are injection molded from propionate, which is superior to other window materials in every significant performance characteristic. They are preformed at the factory to the exact curve of the faceshield crowns for easy installation, an exact fit and a perfect seal. Windows are .060" thick for an extra margin of protection, yet cost no more than ordinary .040" windows. Available in clear and multiple tints for specific applications. Shade 5 protects from Oxy-Fuel welding and cutting; True-View Gray protects from glare and UV outdoors while allowing the wearer to see in natural color.

PART #	DESCRIPTION
4178CL	.060" 8" x 16 1/2" clear, wide view
4199CL	.060" 9 3/4" x 19" clear, extended view
4178IRUV5	.060" 8" x 16 1/2" shade 5, wide view
4178TVGY	.060" 8" x 16 1/2" true view gray, wide view



## MODEL F-400-DC DUAL CROWN PROTECTIVE MASK

Provides extended, wraparound protection for tough working conditions. Broader, deeper, 4" crown and chin protectors provide an extra margin of protection when harsh conditions require it. Made from NORYL, the same material used in our welding helmets, model F-400-DC series protective crowns are stronger, more durable and more heat resistant than ordinary faceshields. Also available with Speedy Loop, Quick-lok, and Quick-Lok Slot Blade mounting devices for protective caps.

PART #	DESCRIPTION
F400DC	Faceshield with chin guard
FM70DC	Cap bracket mount and chin guard

