

# 7655WC

## Barrier-Free Emergency Equipment



### FEATURES & BENEFITS

#### Construction

Type 304 Stainless Steel recessed pull down cabinet design provides a space efficient full functioning piece of emergency equipment in the time of an emergency.

#### Valves

Valve is designed to make the flushing of fluid occur with the pull of the eyewash bends.

#### Added Protection

Barrier-free pull-down design allows for a wide range of users to operate the emergency equipment so everyone has the option of safety.

#### Quality Control

The entire unit is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind.

#### Safety

8" x 10-3/4" universal emergency sign, test card to record weekly testing of emergency equipment, and barrier-free design bring safety to a whole new level.



### OPTIONS

- Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- Tempered Water Blending Valves: Model 9201EF is a thermostatic mixing valve that mixes hot and cold water to supply tempered water to fixtures requiring flow up to 7 gpm @ 30 psi, sufficient for a single eye-eye/face wash. The unit employs a thermostatic mixing element and includes an outlet temperature gauge.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" flow switch when emergency eye/face wash is in use.

### SPECIFICATIONS

Model 7655WC barrier-free eye/face wash shall include a fully recessed wall mounted stainless steel cabinet, green Feather-Flo® ABS plastic eye/face wash heads with integral flow controls and dust covers, polished chrome-plated brass pull-down valve, and brass stay-open supply ball valve equipped with stainless steel ball and stem. Unit shall also include front-access maintenance panel, universal sign, and 1/2" IPS inlet.

### APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face shall be provided within the work area for immediate emergency use. This unit brings a nice finish to any location, all while offering a wide coverage area for the face and eyes. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7655WC is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



# 7656WC

Barrier-Free Emergency Equipment



## FEATURES & BENEFITS

### Construction

Type 304 Stainless Steel recessed pull down cabinet design provides a space efficient full functioning piece of emergency equipment in the time of an emergency.

### Flow Controls

Green ABS Feather-Flo® heads equipped with built-in 2.5 gpm (2) self-regulating flow controls provide multiple soft-and-steady flowing streams of water for a maximum coverage area. Further equipped with front cover/drain pan, unit stays protected from debris up until the last second before use.

### Valve

Valve is designed to make the flushing of fluid occur with the pull of a lever.

### Added Protection

Stainless steel drain pan collects eye/face wash waste within the cabinet so the cleansing area remains as clean as possible throughout the irrigation process. Barrier-free pull-down design allows for a wide range of users to operate the emergency equipment so everyone has the option of safety.

### Quality Control

The entire unit is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind.

### Safety

8" x 10-3/4" universal emergency sign, test card to record weekly testing of emergency equipment, and barrier-free design bring safety to a whole new level.



## SPECIFICATIONS

Model 7656WC barrier-free eye/face wash shall include a fully recessed wall mounted stainless steel cabinet with drain pan, green Feather-Flo® ABS plastic eye/face wash heads with integral flow controls and dust covers, polished chrome-plated brass pull-down valve, and brass stay-open supply ball valve equipped with stainless steel ball and stem. Unit shall also include front-access maintenance panel, universal sign, ½" IPS inlet, and 1-1/2" IPS waste.

## OPTIONS

- Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- Tempered Water Blending Valves: Model 9201EF is a thermostatic mixing valve that mixes hot and cold water to supply tempered water to fixtures requiring flow up to 7 gpm @ 30 psi, sufficient for a single eye-eye/face wash. The unit employs a thermostatic mixing element and includes an outlet temperature gauge.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" flow switch when emergency eye/face wash is in use.

## APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face shall be provided within the work area for immediate emergency use. This unit brings a nice finish to any location, all while offering a wide coverage area for the face and eyes. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7656WC is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



# 7752WC

## Barrier-Free Emergency Equipment



### FEATURES & BENEFITS

#### Antimicrobially Treated

AXION MSR™ eye/face wash heads are antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the heads against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face wash product on the market to feature antimicrobial protection.

#### Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

#### Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind.

#### Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

#### Construction

18 gauge Type 304 Stainless Steel with No. 4 satin finish receptor. Low profile brass trap offers a space efficient and durable design that extends a full 19" from the wall providing a barrier-free standard.

#### Valve

Valve is designed to make the flushing of fluid occur with the push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

### OPTIONS

- Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Patent No. 5,350,112).
- Tempered Water Blending Systems: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- Tempered Water Blending Systems: Model 9201EF is a thermostatic mixing valve that mixes hot and cold water to supply tempered water to fixtures requiring flow up to 7 gpm @ 30 psi ΔP, sufficient for a single eye/eye/face wash. The unit employs a thermostatic mixing element and includes an outlet temperature gauge.
- AXION MSR™ Eyewash: Part Number 0002953155 AXION MSR™ eyewash head option is used to convert the eye/face wash to an eyewash, and is supplied with a 1.3 gpm flow control (part # 0002475339).

To see all options for this model, visit [www.hawesco.com](http://www.hawesco.com).



### SPECIFICATIONS

Model 7752WC wall-mounted barrier-free eye/face wash shall include a stainless steel bracket with a integral stainless steel 11" round bowl, an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, brass stay-open ball valve with stainless steel ball and stem, brass 1-1/4" waste trap, universal sign, and 1/2" IPS inlet.

### APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face shall be provided within the work area for immediate emergency use. This unit brings a nice finish to any location, all while offering a wide coverage area for the face and eyes. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7752WC is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment

