

CUSHION STAT™ with DYNA-SHIELD®

DISSIPATIVE/ANTI-STATIC • "BETTER"

- **Sales Tip:** Ideal product for basic anti-fatigue and antistatic relief in an office or light-duty application.
- **Where to Specify:** Work station environment that requires anti-fatigue relief while working with delicate circuitry or components

- Dissipative /anti-static matting is formulated to absorb static electricity. This matting drains static from worker keeping sensitive circuitry from damage.
- Specially compounded pebble-embossed PVC sponge manufactured with NOTRAX® exclusive Dyna-Shield® protective top layer.
- All four sides are beveled to minimize trip hazards.
- Overall thickness is 3/8 inch.
- Testing is per EOS/ESD Association Draft Standard, "Standard for Protection of Electrostatic Discharge Susceptible Items = Worksurfaces" EOS/ESD-S4, Draft January 1988.
- RTG measured at Moderate and 12% RH, at 10V and 100V = 109 ohms.



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NOTRAX® INDUSTRIAL MATS



Brown

Black

Gray

#825 CUSHION STAT™

Stock Sizes	2' x 3'	3' x 5'	3' x 10'	
Weight (lbs.)	4.1	10.2	19.2	
Roll Sizes & Custom Sizes	3' x 60'	4' x 60'	3' Widths	4' Widths
Weight (lbs.)	114.6	168	.64/sq.ft.	.64/sq.ft.

Shipping Location: Superior Manufacturing Group - Moselle, MS 39459

Black / Yellow





- **Sales Tip:** For maximum effectiveness, we highly recommend that the end-user properly attaches the grounding cord which is included at no charge. It easily snaps into a grommet which is installed in the mat at our factory.
- **Where to Specify:** Assembly or testing areas for circuitry: computers, chips, electronics of all kinds.

- Dissipative /anti-static matting is formulated to absorb static electricity. This matting drains static from worker keeping sensitive circuitry safe from damage.
- Durable vinyl diamond-plate top surface is combined with dense closed cell foam base utilizing NOTRAX® exclusive UniFusion™ technology.
- Provides excellent anti-fatigue support with a textured anti-slip surface
- Overall mat thickness is 9/16 inch.
- Sloped beveled foam on all 4 undersides affords easy access onto and off of mat.
- Custom widths available



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NOTRAX® INDUSTRIAL MATS



Uni FUSION™



Black



#826 DIAMOND STAT™

Stock Sizes	2' x 3'	3' x 5'	3' x 12'
Weight (lbs.)	9	16	38

Roll & Custom Sizes

	3' x 75'	3' Widths	Custom Widths
Weight (lbs.)	320	1.36/sq.ft.	1.36/sq.ft.

Prices include Grounding Cord

Shipping Location: Superior Manufacturing Group - Moselle, MS 39459