

UltraContainment Berms®

Economy Model



Economical Design Offers Cost Savings And Secure Containment

- L-shaped aluminum brackets provide sturdy sidewall support.
- Easy assembly — Brackets are quickly and easily inserted into sleeves spaced around perimeter of Berm.
- No frames, components or excess material outside of sidewalls — excellent for use inside storage sheds and other buildings or structures where floor space is a premium.

• Meets SPCC and EPA Container Storage Regulations 40 CFR 264.175.

ULTRA-CONTAINMENT BERMS, ECONOMY MODEL			
Part#	Dimensions	Weight	Containment Capacity
8250	4' x 6' x 1' (1.2 m x 1.8 m x .3 m)	21 lbs. (9.5 kg)	179 gallons (678 L)
8251	6' x 6' x 1' (1.8 m x 1.8 m x .3 m)	26 lbs. (12 kg)	269 gallons (1,018 L)
8252	10' x 10' x 1' (3.0 m x 3.0 m x .3 m)	52 lbs. (23.5 kg)	748 gallons (2,831 L)
8253	12' x 60' x 1' (3.7 m x 18.3 m x .3 m)	268 lbs. (121.5 kg)	5,385 gallons (20,382 L)
8254	15' x 50' x 1' (4.6 m x 15.2 m x .3 m)	259 lbs. (117.5 kg)	5,610 gallons (21,234 L)
8255	15' x 66' x 1' (4.6 m x 20.1 m x .3 m)	334 lbs. (151.5 kg)	7,405 gallons (28,028 L)

Material of Construction: Copolymer 2000™ an ethylene copolymer, is standard. Copolymer 3000™, XR5, polyurethane and other materials are also available on a custom basis. Options: Ground Tarps, Track Belts, Pull Over Covers. Self Bailer, see page 38.



Compact shipping and storage — with frames removed, Berm requires very little space (10' x 10' unit shown).

UltraContainment Berms®

Collapsible Wall Model



Economical Design Sets Up Quickly — Provides Secure Containment



- The Collapsible Wall Model Containment Berm features rugged PVC sidewall assemblies for sidewall support. Simply swivel the “feet” of the PVC supports to lower or raise the sidewalls in just seconds!
- Custom sizes available.
- Meets SPCC and EPA Container Storage Regulations 40 CFR 264.175.

ULTRA-CONTAINMENT BERMS, COLLAPSIBLE WALL MODEL			
Part#	Dimensions	Weight	Containment Capacity
8405	4' x 6' x 1' (1.2 m x 1.8 m x .3 m)	43 lbs. (19.5 kg)	179 gallons (678 L)
8403	6' x 6' x 1' (1.8 m x 1.8 m x .3 m)	46 lbs. (21 kg)	269 gallons (1,018 L)
8400	10' x 10' x 1' (3.0 m x 3.0 m x .3 m)	70 lbs. (32 kg)	748 gallons (2,831 L)
8404	12' x 60' x 1' (3.7 m x 18.3 m x .3 m)	323 lbs. (147 kg)	5,385 gallons (20,382 L)
8401	15' x 50' x 1' (4.6 m x 15.2 m x .3 m)	319 lbs. (145 kg)	5,610 gallons (21,234 L)
8402	15' x 66' x 1' (4.6 m x 20.1 m x .3 m)	420 lbs. (191 kg)	7,405 gallons (28,028 L)

Material of Construction: Copolymer 2000™ an ethylene copolymer, is standard. Copolymer 3000™, XR5, polyurethane and other materials are also available on a custom basis. Options: Ground Tarps, Track Belts. Self Bailer, see page 38.



Simply swivel the “feet” of the PVC supports to lower the sidewall. Vehicles and equipment can then roll over the top of the collapsed wall for convenient entry and exit.



Rugged design easily contains small and large spills.