Ultra Oil & Debris Blocker

Stop Pollutants Before They Can Reach Stormwater Outflow

- Stormwater is forced to flow through bottom of unit — floating trash and hydrocarbons remain on the water's surface and cut of the outflow.
- Installs quickly and easily in storm drain outflows.
- Low-profile allows vactor trucks to clean catch basin without removing the unit.

		SOLUTION STORMWATER Trash and stormwater enter. Floating debris and oil.	
nm)	4 lbs. (2 kg)	Solids that sink.	J
nm)	6 lbs. (3 kg)	Cicaliei water:	The same of
nm)	6 lbs. (3 kg)		

U.S. Patent Pending

- Dual component, all-polyethylene unit will not rust or corrode.
- Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.

4 lbs. (2 kg)
1 (29)
6 lbs. (3 kg)
6 lbs. (3 kg)
6 lbs. (3 kg)
7 lbs. (3 kg)
2 lbs. (1 kg)
3 lbs. (1.5 kg)

Note: Adapter is required for any 10" and 12" Ultra-Oil & Debris Blocker installation. 8" unit is one piece.

Ultra Drain Guard Retainers

Keep Drain Guards In Place Without The Use Of Grates





- Heavy-Duty coated steel retainers mount on inside ledge of catch basin securing Drain Guard when grating is removed or installed.
- Two sizes of telescoping retainers adjust to fit any size storm drain.
- For use with all Drain Guards.

Part# 9237 Set of two. For catch basins from 36" – 62" (915 mm x 1,575 mm)

Set of two. For catch basins from 36" – 62" (915 mm x 1,575 mm)

Ultra**&&**Drain Markers®

- Helps inform and educate the public that most storm drains go directly into waterways untreated.
- Installs quickly and easily using permanent adhesive — cleaner and more environmentally friendly than paint and stencils.
- Designed for long life heavy-duty plastic construction is scratch-resistant and will not rust or corrode.
- Part # 9208 includes 25 Markers and adhesive.
- Helps comply with NPDES, 40 CFR 122.26 (1999).



