

Anchorage

Connectors



Anchorage connectors are just another example of the wide product assortment offered by North. These types of connectors can be as varied as the places in which they are used. Some are portable, some are designed to move along with the worker and some are fixed. From beam anchors to anti-rollout D-rings, North has you connected.

MOVING ANCHORAGE CONNECTORS



Features/Benefits

- Adjustable to accommodate a wide variety of I-Beams
- Designed for use with self-retracting lifelines on horizontal I-beams
- Removable at any point of the beam
- Travels with user to eliminate the swing fall

Part No	Description
FP05	Beam trolley that mounts anywhere on a suitable metal beam - Minimum turn radius of 12" (30 mm) - Fits widths of 2.3" (50 mm) to 6.5" (165 mm)
FP05EXT	Extends fit of FP05 to 8.5" (190 mm)
FP06	Gliding beam anchor that mounts anywhere on a suitable metal beam - Can be dismantled in seconds and moved to a new location or job site - Lightweight - fits 4" (100 mm) to 12" (300 mm) widths Stainless steel construction with easy-to-use D-ring connector

FLEXIBLE ANCHORAGE CONNECTORS



Features/Benefits

- Design to couple fall arrest lanyard to anchorage
- Each Flexible Anchorage connector has min strength of 5,000lbs (22kN)
- Can be used for a variety of fall arrest applications

Part No	Description	Length
FP02/	Cable Sling - 1/4" (6 mm) galvanized steel cable with swaged eyes at each end - PVC coated against corrosion	3', 4', 5' or 6' (0.9m, 1.2 m, 1.5 m or 2 m)
FP03/	Pass Through Anchor Sling - 2" (50 mm) heavy-duty nylon web with small D-ring which passes through the large D-ring to form loop around anchor	3', 4', 5' or 6' (0.9m, 1.2 m, 1.5 m or 2 m)
FP04/	Pass Through Anchor Sling - 1" (25mm) nylon sling material with 1 D-ring that is used as the anchor connector when the webbing is loop around anchor	3', 4', 5' or 6' (0.9m, 1.2 m, 1.5 m or 2 m)
FP242/	Spectra® Web Loop Sling - Tiny'n Tough (T'nT) Sling is made of revolutionary Spectra webbing for lightweight, small size and exceptional strength - 3/4" (19 mm) web can be used without additional protective materials in concrete forming	2', 3', 4', 5' or 6' (0.6m, 0.9 m, 1.2 m, 1.5 m or 2 m)
FP09/3	Residential anchor sling - heavy-duty nylon web	3' (0.9m)

Available Only in Canada

FIXED ANCHORAGE CONNECTORS



Features/Benefits

- D-ring shape reduces rollout possibilities
- Mounting hardware required

Part No	Construction	Gate Opening (W)	Width (X)	Length (Y)
FP3730	Bolt on D-ring	4-1/4" (197 mm)	2-15/16" (75 mm)	2-13/16" (71 mm)