



### Tank Top Lifts

- Provides easy access to tank trucks, railroad cars or other applications
- For use on hard level surfaces
- 48" long cantilevered platforms
- Hydraulic hand pump raises and lowers platform
- Step and deck tread is open serrated grating, while slip resistant rungs provide access when platform is raised
- Base is 28" wide and 60" long, fixed outriggers spread 69"
- Full rails on both sides with gates at each end
- Recommended Option: 30" extension railing
- Manually propelled
- Two swivel and two rigid 8" casters for use on hard surfaces
- Two adjustable stabilizing jacks secure lifts to ground
- Available with a fixed platform height
- 300 lbs. load capacity
- Standard finish deep gray enamel paint, safety orange also available



*\*Note: If you have a slower internet connection please allow the video to download first to ensure uninterrupted viewing.*



**Shown with special purpose modifications**

**Great for all kinds of maintenance applications.**

***Can be modified to suit your needs.***

Model	Platform	Height	Platform	Platform	Underclearance	Weight	Three available power options:
-------	----------	--------	----------	----------	----------------	--------	--------------------------------

Number	Max	Min	Length	Width	Height	Lbs.
TT-913	13' 8 "	9' 4"	48"	24"	Adjustable 9' to 13'	1525
TT-913F	13' 8 "	9' 4"	48"	24"	Non-Adjustable 9' to 13'	1450

#### OPTIONAL ACCESSORIES

AC electric power  
DC electric power  
Air-Hydraulic power  
Tool Tray  
Fluorescent tube holder  
Platform duplex receptacle  
Removable 30" extension railing  
Safety orange enamel paint finish

- Convenient plug in 120V AC with thermal overload protection and dual contactors for additional safety  
- Independent 12V DC deep cycle system complete with battery and charger along with a double solenoid for additional safety  
- Air hydraulic power requiring 90 CFM with 90 PSI pressure



Manually propelled scissor lifts available up to 33' working heights

Call for specifications, pricing and availability.

**Return Policy:** Written factory permission must be received prior to return. Returns must be in good condition and made within 30 days of original shipment. Freight prepaid. Restocking charge of 20% on standard lifts. Restocking charge of 25% on standard lifts with power option

**Minimum Order:** \$15.00: Prepay and add shipments are subject to \$5.00 service charge.

**Non-Returnable Items:** Custom or air hydraulic lifts.

