Slimline & Mini-veyors


Economical units designed for light duty applications. Ideal for small parts handling where space is limited. The slimline conveyor side guard construction is perfect for transporting materials in confined spaces, while the mini-veyor has no guard rail. Can be used for assembly line operation. Stainless frame available.




SL & BMV SERIES SPECIFICATIONS:

1/4 HP 110/1/60 Gear Motor • 14 Ga. Formed Bed • 3 Ply Brown Neoprene Belt • 60 FPM Standard • 2" Drive Pulley • Capacity: 100 lbs. Other Speeds Available • See page 21 for electrical controls

For electrical controls see page 21.






> SL SERIES

			WEIGHT		
Model No	Belt Width In	Bed Width In	5 Ft Lbs	10 Ft Lbs	
SL-06	6	7	150	255	
SL-12	12	13	190	323	
SL-18	18	19	225	382	
SL-24	24	25	270	458	

BMV SERIES

			WEIGHT		
Model No	Belt Width In	Bed Width In	5 Ft Lbs	10 Ft Lbs	
BMV-06	6	7	148	251	
BMV-12	12	13	186	316	
BMV-18	18	19	220	374	
BMV-24	24	25	264	448	





PBV SERIES SPECIFICATIONS:

1/4 to 1/2 HP 110/1/60 Gear Motor ◆ 14 Ga. Formed Bed ◆ 60 FPM ◆ 4" Drive Pulley ◆ 1-1/2" High Cleats on 12" Centers ◆ Top Mounted End Drive ◆ Black PVC Belt

For electrical controls see page 21.

PBV SERIES

			WEIGHT			
Model No	Belt Width In	Bed Width In	Over-All Length: 5 Ft	Over-All Length: 7 Ft	Over-All Length: 9 Ft	Over-All Length: 11 Ft
PBV-08	8	12	440	485	530	574
PBV-12	12	16	480	522	564	605
PBV-16	16	20	585	635	685	735