

Self-Retracting Lifeline



North's self retracting lifelines (SRL) continue to provide versatile performance for fall arrest. Robust design, a variety of lifeline lengths and corrosion resistant alloy housing means your SRL investment will go a long way. Units can be equipped with stainless steel cables, or non-conductive Dyneema® rope as standard (or with galvanized cables on request.. Note: stainless steel cable is ideal for the food industry and environments involving chemicals. All are equipped with a load indicator that triggers to show the unit has been subjected to a severe force.

North's range is of a modular design. The materials used are characterised by a high corrosion resistance, a high strength and a relatively low weight. The blocks are constructed in a way that they can be disassembled and hence maintained. These features all ensure a wide usability and a long lifetime.

SELF RETRACTING LIFELINE



Features/Benefits

- Lifeline retracts under light tension
- Excellent for ladder climbing to keep the lifeline out of the way
- Multiple use - universal application
- Hands free vertical mobility
- Easy to use and install
- Minimizes fall distance
- Variety of lengths to choose from
- Increased user mobility in work area

Part No	Lifeline Type	Length	Weight
Small housing			
FP1/305S	3/16" (5 mm) stainless cable with swivel load indicating snap hook	16ft (5 m)	9.5lbs (4.3 kgs)
Regular housing			
FP2/310S	3/16" (5 mm) stainless cable with swivel load indicating snap hook	33ft (10 m)	16lbs (7.3 kgs)
FP2/315S	3/16" (5 mm) stainless cable with swivel load indicating snap hook	50ft (15 m)	18lbs (8.2 kgs)
FP2/315K	1/4" (6 mm) Dyneema cable with swivel load indicating snap hook	45ft (14 m)	16lbs (7.3 kgs)
Large housing			
FP3/320S	3/16" (5 mm) stainless cable with swivel load indicating snap hook	65ft (20 m)	29.5lbs (13.4 kgs)
FP3/325S	3/16" (5 mm) stainless cable with swivel load indicating snap hook	82ft (25 m)	31 lbs (14 kgs)
FP3/333S	3/16" (5 mm) stainless cable with swivel load indicating snap hook	110ft (33 m)	33lbs (15 kgs)
FP3/325K	1/4" (6 mm) Dyneema cable with swivel load indicating snap hook	82ft (25 m)	31 lbs (14 kgs)

NOTE: For galvanized cable, please call us for special orders.

ACCESSORIES



Part No	Description
FP3TL	Tag line for remote extraction and retraction of the cable
FP86	Drop forged D-shaped carabiner - 3/4" (19 mm) gate opening
FP88	Auto locking carabiner, large gate opening 29/32" (23 mm)

FP88
* Use on FP2 & FP3 series SRL