### **Portable Scissor Lift Tables**

Heavy-duty powered lift tables are designed to transport and elevate your heaviest loads. A heavy-duty 12V DC power unit with deep cycle battery and an on-board battery charger is standard, a battery charge indicator is optional. Features 8" phenolic casters (2 swivel and 2 rigid), floor lock, and patented electric pinch point guards. Push buttons to raise and lower lift, located on power unit and in the pendant-style push-button control, are standard. Key-operated ON/OFF control for better security is built into the power unit. Minimum frame width is 34". Add 25" to platform length for the overall length.

#### Model Number Format PST - (width)(length) - capacity - raised height

VERTICAL TRAVEL	PLATFORM WIDTH	PLATFORM Length	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	TRAVEL TIME (SEC)	NET WT. (POUNDS)
36"	24" - 48"	48" - 72"	1,000	46"	10"	9	1408
36"	24" - 48"	48" - 72"	2,000	46"	10"	14	1437
36"	24" - 48"	48" - 72"	3,000	46"	10"	20	1491
48"	24" - 48"	64" - 90"	1,000	58"	10"	14	1496
48"	24" - 48"	64" - 90"	2,000	58"	10"	20	1580
48"	24" - 48"	64" - 90"	3,000	58"	10"	28	1780

PORTABLE SCISSOR TABLE OPTIONS				
MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)		
PST-HC	HAND HELD PENDANT CONTROL ON 8 FT. COIL CORD	1		
PST-AC	24V HAND CONTROL WITH 115V 1 PHASE MOTOR			
PST-AIR*	FACTORY AIR OVER OIL (W/FOOT TREADLE CONTROL (FRL REQ'D)*)			
PST-FP	MANUAL FOOT PUMP OPTION			
PST-PTDS	POWER TRACTION DRIVE SYSTEM	156		
BC	BENCH TOP STYLE BATTERY CHARGER	8		
BCI	BATTERY CHARGE INDICATOR GAUGE	1		
*FILTER REGULAT	OR - LUBRICATOR REQUIRED TO OPERATE (WARRANTY VOID WITHOUT)	*		

# **Power Traction Drive System**

Reduce worker fatigue and injury with the Portable Traction Drive Option. This factory installed option is available on portable equipment including the Portable Scissor Table, Pallet Master/Pallet Server, Tilt Master, and High Rise Lift Truck. An alternative to costly fork trucks, the PTDS includes a combination throttle / direction butterfly style controller, an adjustable yoke and an auto reverse emergency "belly" switch. This state of the art option allows a single operator to safely and ergonomically transport products. Power pack is 42" wide. Maximum speed is 2.5 m.p.h.

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
PTDS	POWER TRACTION DRIVE SYSTEM	156



DVD or VIDEO AVAILABLE

TILT MASTER STRADDLE WITH PTDS OPTION



PALLET MASTER/PALLET SERVER WITH PTDS OPTION



PORTABLE SCISSOR TABLE WITH PTDS OPTION

# Air Bag Scissor Lift Tables

Air Bag Scissor Lift Tables use factory air for clean, dependable, maintenance free operation. Designed to raise products up to an ergonomic working height. Safety features include pressure relief and pinch point guard. Must be used in conjunction with a filter/regulator. We do not recommend the use of a lubricator. Includes hand held control with up and down button mounted on 8 ft. cord. Incoming air must be clean, dry and regulated to 80 psi (min.). Requires 1/2" incoming airline. Standard features are adjustable upper travel limit valve, state-of-the-art lifetime lubricated bearings and maintenance prop. Other sizes available, contact factory.

#### Model Number Format ABLT - (width)(length) - capacity - raised height

			• /			•	
VERTICAL Travel	PLATFORM WIDTH	PLATFORM Length	CAPACITY (POUNDS)	RAISED Height	LOWERED HEIGHT	TRAVEL TIME (SEC.)	NET WT. (POUNDS)
28"	42" - 60"	48" - 72"	2,000	36"	8"	14	897
28"	42" - 60"	48" - 72"	4,000	36"	8"	28	942
OPTIONAL FOOT CONTROL, MODEL ABLT-FC							



