

Fixed and Adjustable Steel Gantry Crane Options




FESTOON SYSTEM
model AHA-FES-KIT

STEEL GANTRY CRANE OPTIONS

MODEL NUMBER	DESCRIPTION
AHS-2/4-TLC	TOTAL LOCKING CASTERS (FOR 2,000 & 4,000 LBS. CAPACITY CRANES ONLY) (SET OF 4)
AHS-6/8-TLC	TOTAL LOCKING CASTERS (FOR 6,000 LB. & 8,000 LBS. CAPACITY CRANES ONLY) (SET OF 4)
AHS-2/4-V**	8" x 2" V-GROOVE CASTERS FOR 2,000 & 4,000 LBS. UNITS (SET OF 4)
AHS-6/8-V**	8" x 3" V-GROOVE CASTERS FOR 6,000 & 8,000 LBS. UNITS (SET OF 4)
AHS-KIT	(2) COME-A-LONGS FOR HEIGHT ADJUSTMENT (NOT FOR LIFTING)

**4-POSITION V-GROOVE CASTERS AVAILABLE UPON REQUEST, CONTACT FACTORY



Steel Gantry Crane Power Traction Drive Options

MODEL NUMBER	DESCRIPTION
GPTD-2	2,000 TO 4,000 LBS. CAPACITY / STANDARD WITH 3 BUTTON HAND CONTROL
GPTD-4	6,000 TO 8,000 LBS. CAPACITY / STANDARD WITH 3 BUTTON HAND CONTROL
V-TRACK	10 FOOT SECTION OF V-GROOVE TRACK

ADDITIONAL BUTTONS ON HAND CONTROL FOR HOIST & TROLLEY AVAILABLE, CONTACT FACTORY

Adjustable Height Aluminum Gantry Cranes

The Adjustable Height Aluminum Gantry Crane combines lightweight and rigid construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. The lightweight I-beam allows height adjustment without the need of a hoist or fork truck. All pinned connections make it possible for two people to set up. Height is adjustable in 6" increments. Hoist and trolley can be ordered separately, see pages 90-92.

Note: All products should be inspected frequently to insure safe operation. Final testing and inspection is left to end user after final assembly has been completed. For further details see ASME B30.17.



FESTOON SYSTEM
model AHA-FES-KIT



TOTAL LOCKING
model AHA-2/4-TLC



PNEUMATIC CASTERS
model AHA-PNU



"V" GROOVE
model AHA-2/4-V



ADJUSTABLE HEIGHT



ADJUSTABLE SPAN



STANDARD 4-POSITION
8" PHENOLIC SWIVEL
CASTER

MODEL NUMBER	CAPACITY (POUNDS)	OVERALL BEAM LENGTH / HEIGHT	UNDER I-BEAM RANGE	BASE WIDTH	FLANGE WIDTH	NET WT. (POUNDS)
AHA-2-8-10*	2,000	8' / 6"	7'8" to 10'2"	54"	3.75"	280
AHA-2-8-12*	2,000	8' / 6"	9'6" to 12'	54"	3.75"	295
AHA-2-10-10*	2,000	10' / 6"	7'8" to 10'2"	54"	3.75"	294
AHA-2-10-12*	2,000	10' / 6"	9'6" to 12'	54"	3.75"	310
AHA-2-12-10	2,000	12' / 8"	7'8" to 10'2"	54"	4"	325
AHA-2-12-12	2,000	12' / 8"	9'6" to 12'	54"	4"	340
AHA-4-8-10	4,000	8' / 8"	7'8" to 10'2"	54"	4"	360
AHA-4-8-12	4,000	8' / 8"	9'6" to 12'	54"	4"	375
AHA-4-10-10	4,000	10' / 8"	7'8" to 10'2"	54"	4"	405
AHA-4-10-12	4,000	10' / 8"	9'6" to 12'	54"	4"	431
AHA-4-12-10	4,000	12' / 8"	7'8" to 10'2"	54"	4.125"	421
AHA-4-12-12	4,000	12' / 8"	9'6" to 12'	54"	4.125"	446

USABLE DISTANCE BETWEEN UPRIGHTS IS OVERALL BEAM LENGTH MINUS 24" / 14 1/2"

USABLE TROLLEY TRAVEL LENGTH IS OVERALL BEAM LENGTH MINUS 20"

ALUMINUM GANTRY CRANE OPTIONS

MODEL NUMBER	DESCRIPTION
AHA-2/4-TLC	TOTAL LOCKING CASTERS (FOR 2,000 & 4,000 LBS. CAPACITY CRANES ONLY) (SET OF 4)
AHA-PNU	FOUR-WAY LOCK 12" x 3 1/2" PNEUMATIC CASTERS (1,500 LBS. CAPACITY)
AHA-PNU-RF	RETROFIT FOUR-WAY LOCK PNEUMATIC CASTERS (1,500 LBS. CAPACITY)
AHA-2/4-V	8" x 2" V-GROOVE WHEELS (FOR 2,000 & 4,000 LBS. UNITS) (SET OF 4)
AHA-2/4-V4	8" x 2" V-GROOVE WHEELS (FOR 2,000 & 4,000 LBS. UNITS) (W/4-POSITION LOCK) (SET OF 4)
AHA-KIT	(2) COME-A-LONG FOR HEIGHT ADJUSTMENT (NOT FOR LIFTING)
AHA-FES-KIT	FESTOON KIT, 115V AC POWER