

Dock Seals

Designed for maximum energy savings with long-lasting features

For use with an 8'W x 8'H (D-150-XX) or 8'W x 9'H (D-350-XX) door. Superior 36 oz. nylon reinforced vinyl facing has a higher tear strength than equivalent weight hypalon. Chemically sealed ends prevent moisture infiltration. Full height air escape tunnel. Mounted and bonded on durable wolmanized wood. 2" nylon reinforced guide stripes. Through-the-wall installation kits included. Three piece construction: top - 12" high; sides - beveled sides with 9½" width at the wall and 12" width at the face. 5" maximum compression is recommended. Applications with a flush dock to building in conjunction with an Edge-O-Dock use a 20" projection* Dock Seal. To ensure proper size complete and fax the survey sheet shown on page 8. Units are non-returnable.



MODEL NUMBER	PROJECTION	OVERALL HEIGHT	OVERALL WIDTH	NET WT. (POUNDS)
DOOR SIZE 8 FEET WIDE x 8 FEET HIGH				
D-150-10	10"	108"	120"	230
D-150-11	11"	108"	120"	242
D-150-12	12"	108"	120"	253
D-150-13	13"	108"	120"	265
D-150-14	14"	108"	120"	276
D-150-15	15"	108"	120"	288
D-150-16	16"	108"	120"	299
D-150-17	17"	108"	120"	311
D-150-18	18"	108"	120"	322
D-150-19	19"	108"	120"	334
D-150-20*	20"	108"	120"	345

MODEL NUMBER	PROJECTION	OVERALL HEIGHT	OVERALL WIDTH	NET WT. (POUNDS)
DOOR SIZE 8 FEET WIDE x 9 FEET HIGH				
D-350-10	10"	120"	120"	259
D-350-11	11"	120"	120"	270
D-350-12	12"	120"	120"	282
D-350-13	13"	120"	120"	293
D-350-14	14"	120"	120"	305
D-350-15	15"	120"	120"	316
D-350-16	16"	120"	120"	328
D-350-17	17"	120"	120"	351
D-350-18	18"	120"	120"	362
D-350-19	19"	120"	120"	374
D-350-20*	20"	120"	120"	399

Dock Seal/Shelter Combinations

For use with an 8'W x 10'H door. Top (header) is constructed of wolmanized lumber and is built with a slope to allow for water run-off. Header measures 114"W with a 30" drop curtain. Side (verticals) measure 120" tall and contain high density foam mounted to treated lumber. Once mounted, the face of the vertical will measure 12"W and will taper to 9½" at wall. Verticals are mounted on 2" x 12" wooden boards allowing wall mounting down the length of the vertical pieces. Applications with a flush dock to building in conjunction with an Edge-O-Dock use a 20" projection* Dock Seal. To ensure proper size complete and fax the survey sheet shown on page 8. Units are non-returnable.

MODEL NUMBER	PROJECTION	OVERALL HEIGHT	OVERALL WIDTH	NET WT. (POUNDS)
DOOR SIZE 8 FEET WIDE x 10 FEET HIGH				
D-150/650-10	10"	126"	114"	240
D-150/650-11	11"	126"	114"	254
D-150/650-12	12"	126"	114"	266
D-150/650-13	13"	126"	114"	301
D-150/650-14	14"	126"	114"	315
D-150/650-15	15"	126"	114"	327
D-150/650-16	16"	126"	114"	340
D-150/650-17	17"	126"	114"	352
D-150/650-18	18"	126"	114"	365
D-150/650-19	19"	126"	114"	379
D-150/650-20*	20"	126"	114"	395

Dock Shelters

For use with doors up to 10'W x 10'H. Reduces oversized doors to match truck opening. Long wear Vestex V-42 fabric is highly resistant to abrasion and tearing. Fiberglass staves are sewn into the flaps. Seal is formed along the sides and top of trailer when the vertical and top panels are pushed inward by the trailer. Recommend minimum 10" trailer penetration for a good seal. Supporting structure is made of 2" x 4" wolmanized lumber. Shelter is protected by safety yellow steel guide protectors. The top header piece measures 132"W and contains a drop curtain which measures 36"H. Two vertical pieces measure 126" tall with vertical flaps measuring 21"W. When installed, the shelter will close the door opening down to 90"W x 90"H (between flaps). Includes two yellow steel guide protectors and foam-filled corner pads for extra sealing action. To ensure proper size complete and fax the survey sheet shown on page 8. Units are non-returnable.

MODEL NUMBER	PROJECTION	OVERALL HEIGHT	OVERALL WIDTH	NET WT. (POUNDS)
DOOR SIZE 8 FEET WIDE x 8 FEET HIGH to 10 FEET WIDE x 10 FEET HIGH				
D-750-18	18"	126"	132"	338
D-750-24	24"	126"	132"	368
D-750-30	30"	126"	132"	397
D-750-36	36"	126"	132"	427



- Effective sealing action with full height access.
- This versatile unit utilizes seal sides and a shelter top.

DOCK SEAL & SHELTER OPTIONS & SURVEY SHEET CAN BE FOUND ON PAGE 8



- White translucent sides allow natural light in dock area.
- Ideal for trucks with varying heights, where the entire truck opening must be accessible for loading.