

Reel Racks

Store and dispense poly or wire rope, hose, electrical cable, or chain. 96" units have 3 pairs of axle brackets; 120" units have 4 pairs of axle brackets (additional brackets available, contact factory). The axle brackets are adjustable on 2" centers and accept axles up to 2¼" in diameter. Adjustable brackets allow you to stagger arms along the frame for different size reels. Axles are included with reel rack. Capacity per level is 2,000 pounds when evenly distributed. Assembly required. Units must be secured to floor.

MODEL NUMBER	OVERALL WIDTH	OVERALL DEPTH	OVERALL HEIGHT	INCLINE	TOTAL CAPACITY (POUNDS)	NET WT. (POUNDS)
STARTER KITS						
RERC-338	39"	36"	96"	71°	6,000	169
RERC-438	51"	36"	96"	71°	6,000	178
RERC-3310	39"	36"	120"	75°	6,000	212
RERC-4310	51"	36"	120"	75°	6,000	223
ADD-ON SECTIONS						
RERC-A-338	39"	36"	96"	71°	6,000	110
RERC-A-438	51"	36"	96"	71°	6,000	119
RERC-A-3310	39"	36"	120"	75°	6,000	137
RERC-A-4310	51"	36"	120"	75°	6,000	148



New




Wire Reel Caddy

Portable Wire Reel Caddy is designed to easily move wire reels where you need them the most. Dispense wire in vertical or horizontal position. Includes four spool bars for handling various size reels. Bottom of caddy includes wire guide holes for quick access. Built-in hand hole for portability. Steel construction with painted finish. Optional hand truck is available for easy transportation.

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x L x H)	NET WT. (LBS.)
WIRE-D	STAND-ALONG UNIT	24" x 16" x 44"	45
WIRE-D-WHK	PORTABLE UNIT (CASTERS & HANDLE)	24" x 16" x 51¼"	51
WIRE-D-SHD-PN	HAND TRUCK (PNEUMATIC WHEELS)	24" x 19" x 52"	51
WIRE-D-SHD-HR	HAND TRUCK (HARD RUBBER WHEELS)	24" x 19" x 52"	64

New



Wire reels are not included.

WIRE-D shown with WIRE-D-SHD-HR



Non-Flammable Safety Cabinets

All welded double wall 18 gauge inside construction, 14 gauge outside construction with 1½" insulating air space. Each unit contains 2" leakproof sill to contain leaks. Lockable flush mounted handle (gripper pad) with 2 keys included. Adjustable leveling feet for various floor surfaces. Galvanized steel shelves adjust on 2½" centers. Manual close doors open to a full 180°. Self close doors shut, index, and latch automatically as fusible link melts under fire conditions at 165°. Meets OSHA and NFPA code 30 standards. Powder coated yellow finish.

MODEL NUMBER	OVERALL SIZE (W x D x H)	CAPACITY (GALLONS)	NUMBER OF SHELVES	DOOR TYPES	NET WT. (LBS.)
TWO DOORS					
VBM-22	34" x 18" x 35"	22	1	MANUAL	170
VBM-30	43" x 18" x 44"	30	1	MANUAL	240
VBM-45	43" x 18" x 65"	45	2	MANUAL	330
VBM-90	43" x 34" x 65"	90	2	MANUAL	440
VBS-30	43" x 18" x 44"	30	1	SELF CLOSE	250
VBS-45	43" x 18" x 65"	45	2	SELF CLOSE	340
ONE DOOR					
VBA-12	23" x 18" x 35"	12	--	MANUAL	140
VBA-16	23" x 18" x 44"	16	--	MANUAL	170
VBA-24	23" x 18" x 65"	24	--	MANUAL	230
VBJ-12	23" x 18" x 35"	12	--	SELF CLOSE	148
VBJ-16	23" x 18" x 44"	16	--	SELF CLOSE	178
VBJ-24	23" x 18" x 65"	24	--	SELF CLOSE	238
55 GALLON DRUM - TWO DOORS					
VBV-1	34" x 34" x 65"	--	--	MANUAL	366
VBV-2	59" x 34" x 65"	--	--	MANUAL	520
VBW-1	34" x 34" x 65"	--	--	SELF CLOSE	386

New



model VBM-45

New



model VBA-16