

## Aluminum Yard Ramps

- 18" x 5" Mold-On-Rubber Tires (standard)
- 4" Curb Height
- Safety Pressure Relief Valve
- Service Height Range is 45" to 62"
- Safety Anchor Chains
- Hand Pump Hydraulic Lift
- Fork Towbar Loop Standard



ALUMINUM GRATING  
series AY



STEEL GRATING  
series SY

Portable Aluminum Yard Ramps have a unique design that allows one person to position the ramp, adjust its service height, and load or unload trailers from ground level. Available with steel or rust resistant aluminum grating.

ALUMINUM YARD RAMP WITH STEEL GRATING					
MODEL NUMBER	CAPACITY (POUNDS)	OVERALL WIDTH	USABLE WIDTH	LENGTH (FEET)	NET WT. (POUNDS)
SY-167230	16,000	72"	66"	30	3518
SY-168430	16,000	84"	78"	30	4043
SY-169330	16,000	93"	87"	30	4515
SY-167236-L	16,000	72"	66"	36	4305
SY-168436-L	16,000	84"	78"	36	4830
SY-169336-L	16,000	93"	87"	36	5303
SY-207230	20,000	72"	66"	30	3623
SY-208430	20,000	84"	78"	30	4148
SY-209330	20,000	93"	87"	30	4620
SY-207236-L	20,000	72"	66"	36	4410
SY-208436-L	20,000	84"	78"	36	4935
SY-209336-L	20,000	93"	87"	36	5408
SY-257230	25,000	72"	66"	30	3675
SY-258430	25,000	84"	78"	30	4200
SY-259330	25,000	93"	87"	30	4725
SY-257236-L	25,000	72"	66"	36	4463
SY-258436-L	25,000	84"	78"	36	4988
SY-259336-L	25,000	93"	87"	36	5513
SY-307230	30,000	72"	66"	30	3728
SY-308430	30,000	84"	78"	30	4253
SY-307236-L	30,000	72"	66"	36	4515
SY-308436-L	30,000	84"	78"	36	5040

ALUMINUM YARD RAMP WITH ALUMINUM GRATING					
MODEL NUMBER	CAPACITY (POUNDS)	OVERALL WIDTH	USABLE WIDTH	LENGTH (FEET)	NET WT. (POUNDS)
AY-167230	16,000	72"	66"	30	2783
AY-168430	16,000	84"	78"	30	3150
AY-169330	16,000	93"	87"	30	3465
AY-167236-L	16,000	72"	66"	36	3360
AY-168436-L	16,000	84"	78"	36	3728
AY-169336-L	16,000	93"	87"	36	3990
AY-207230	20,000	72"	66"	30	2888
AY-208430	20,000	84"	78"	30	3255
AY-209330	20,000	93"	87"	30	3570
AY-207236-L	20,000	72"	66"	36	3465
AY-208436-L	20,000	84"	78"	36	3833
AY-209336-L	20,000	93"	87"	36	4095
AY-257230	25,000	72"	66"	30	2940
AY-258430	25,000	84"	78"	30	3308
AY-259330	25,000	93"	87"	30	3675
AY-257236-L	25,000	72"	66"	36	3578
AY-258436-L	25,000	84"	78"	36	3885
AY-259336-L	25,000	93"	87"	36	4200
AY-307230	30,000	72"	66"	30	3092
AY-308430	30,000	84"	78"	30	3360
AY-307236-L	30,000	72"	66"	36	3570
AY-308436-L	30,000	84"	78"	36	3938



18" x 5" MOLD-ON-RUBBER TIRES ARE STANDARD



HAND PUMP HYDRAULIC LIFT STANDARD



15" OVERLAP INTO TRAILER/BUILDING SAFETY CHAINS STANDARD



PNEUMATIC TIRES OPTION  
Service Range will be 40" to 66"  
model AY-PNTR  
model SY-PNTR

6" CURB HEIGHT OPTION  
suffix CRB6

YELLOW SAFETY CURBS OPTION  
suffix YEL

LOADING DOCK EQUIPMENT