

# PORTABLE EXTINGUISHERS

10520/POT  
BuyLine 5126

**COMMERCIAL  
GRADE  
EXTINGUISHERS  
WITH METAL  
VALVES**



**ABC DRY CHEMICAL**

**HALOTRON 1**

**WATER/FOAM**

**BC DRY CHEMICAL**

**CARBON DIOXIDE**

**ABC MULTI-PURPOSE DRY CHEMICAL:** Used to provide protection against class A, B, and C fires; Red, glossy, polyester-coated steel cylinder with pressure gauge, wall mounting bracket, and hose or nozzle as indicated. Contents stored under pressure at approximately 195 P.S.I.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
3002	2 1/2 lbs.	1A:10B:C	YES	14 3/4"	3"	9'-15'	Nozzle
3005	5 lbs.	2A:10B:C	YES	15 1/4"	4 1/4"	12'-18'	Hose
3005-3	5 lbs.	3A:40B:C	NO	15 1/4"	4 1/4"	12'-18'	Hose
3006	6 lbs.	3A:40B:C	YES	16"	5"	15'-21'	Hose
3010	10 lbs.	4A:60B:C	YES	20"	5"	15'-21'	Hose
3020	20 lbs.	20A:120B:C	YES	23 1/4"	7"	15'-21'	Hose

OPTIONAL MOUNTING BRACKETS	FITS SIZE
3901	5 lb.
3902	6 lb.
3903	10 lb.
3904	20 lb.
3909	5, 6, 10 lb.
3910	20 lb.

**HALOTRON 1:** EPA approved "Clean Agent" for class A, B, and C fires; Red, glossy, polyester-coated steel cylinder with discharge nozzle and bracket. Contents pressurized at approximately 125 P.S.I.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
3101	1.4 lbs.	1B:C	NO	10"	2 7/8"	6'-8'	Nozzle
3102	2.5 lbs.	2B:C	NO	14 3/4"	3"	6'-10'	Nozzle
3105	5 lbs.	5B:C	NO	15 1/4"	4 1/4"	9'-15'	Nozzle
3111	11 lbs.	1A:10B:C	NO	21 1/2"	6"	9'-15'	Hose & Nozzle
3115	15.5 lbs.	2A:10B:C	NO	21 1/2"	6"	12'-18'	Hose & Nozzle

**Call for information  
on water mist  
"Clean Agent"  
and wet chemical  
"Kitchen Use"  
extinguishers**

**PRESSURIZED WATER/FFFP FOAM\*:** Used to provide protection against class A fires; Stainless steel shell with pressure gauge and wall mounting bracket (foam unit furnished with combination cartridge holder, cartridge, and nozzle). Shipped empty, to be charged at destination by authorized personnel.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
3202 (Water)	2 1/2 gals.	2A	YES	24 1/2"	7"	45'-55'	Hose
3252 (Foam)	2 1/2 gals.	3A:20B	NO	24 1/2"	7"	10'-15'	Hose

OPTIONAL MOUNTING BRACKETS	FITS SIZE
3904	2 1/2 gals.

\***OPTION: -AF** Anti-freeze charge

**BC DRY CHEMICAL:** Used to provide protection against class B and C fires; Same as multi-purpose shown above.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
3302	2 1/2 lbs.	10B:C	YES	14 3/4"	3"	9'-15'	Nozzle
3305	5 lbs.	10B:C	YES	15 1/4"	4 1/4"	12'-18'	Nozzle
3305-3	5 1/2 lbs.	40B:C	NO	15 1/4"	4 1/4"	12'-18'	Hose
3306	6 lbs.	40B:C	YES	16 3/4"	5"	15'-21'	Hose
3310	10 lbs.	60B:C	YES	20"	5"	15'-21'	Hose
3320	20 lbs.	120B:C	YES	23 1/4"	7"	15'-21'	Hose

OPTIONAL MOUNTING BRACKETS	FITS SIZE
3901	5 lb.
3902	6 lb.
3903	10 lb.
3904	20 lb.
3909	5, 6, 10 lb.
3910	20 lb.

**CARBON DIOXIDE:** Used to provide protection against class B and C fires; Red, glossy, polyester-coated aluminum cylinder, with discharge horn and wall bracket. Contents pressurized at approximately 735 P.S.I.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	OVERALL WIDTH	RANGE OF STREAM	TYPE DISCHARGE
3405	5 lbs.	5B:C	YES	17 3/4"	5 1/4"	8 1/4"	3'-8'	Horn
3410	10 lbs.	10B:C	YES	24"	7"	12"	3'-8'	Hose & Horn
3415	15 lbs.	10B:C	YES	30"	7"	12"	3'-8'	Hose & Horn
3420	20 lbs.	10B:C	YES	30"	8"	13"	3'-8'	Hose & Horn

OPTIONAL MOUNTING BRACKETS	FITS SIZE
3903	5 lb.
3904	10, 15 lb.
3905	20 lb.
3909	5 lb.