## **Hydraulic Drum Dumpers**

The Hydraulic Drum Dumper is what you need to dump drums that weigh up to 1,500 pounds. Works with 55 and 30-gallon plastic, steel, and fiber drums. The unit has a solid steel chute. Portable units have two rigid and two swivel casters with floor lock screws. All steel construction.

Standard features include: 56 frame, 3/4 HP motor, 120V single phase, 60hz with an 8 foot long power cord and plug. Upper travel limit switch, emergency brass safety velocity fuse in cylinder, and vertical adjustment drum restraints are standard. Chute is rotated with a hand held control on an 8 ft. long coil cord standard.

SSC upgrade is constructed with type 304 Stainless Steel in a Mill Finish. Includes stainless steel chute and base plate. Chute is painted with Steel-It™ coating on back of chute. Adjustable height clamps are stainless steel. Frame is painted enamel blue. This option must be ordered with Drum Dumper.

PORTABLE HYDRAULI	C DRUM DUMPE	RS			
MODEL Number	DUMP Height	ROTATION Height	LEVEL HEIGHT	CAPACITY (POUNDS)	NET WT. (POUNDS)
HDD-36-7-P	36"	91¾"	601/4"	750	798
HDD-48-7-P	48"	113¾"	721/4"	750	871
HDD-60-7-P	60"	1341⁄4"	841/4"	750	966
HDD-72-7-P	72"	155¾"	971/4"	750	1008
HDD-36-10-P	36"	91¾"	601/4"	1,000	819
HDD-48-10-P	48"	113¾"	721/4"	1,000	892
HDD-60-10-P	60"	1341⁄4"	841/4"	1,000	997
HDD-72-10-P	72"	155¾"	971/4"	1,000	1039
HDD-36-15-P	36"	91¾"	601/4"	1,500	960
HDD-48-15-P	48"	113¾"	721/4"	1,500	1023
HDD-60-15-P	60"	1341⁄4"	841/4"	1,500	1128
HDD-72-15-P	72"	155¾"	971/4"	1,500	1176
STATIONARY HYDRAU	JLIC DRUM DUM	PERS			
HDD-36-7-S	36"	91¾"	601/2"	750	735
HDD-48-7-S	48"	1121/4"	721/2"	750	876
HDD-60-7-S	60"	132¾"	841/2"	750	971
HDD-72-7-S	72"	153"	96"	750	1013
HDD-36-10-S	36"	91¾"	601/2"	1,000	824
HDD-48-10-S	48"	1121/4"	<b>72</b> ½"	1,000	897
HDD-60-10-S	60"	132¾"	841/2"	1,000	1002
HDD-72-10-S	72"	153"	96"	1,000	1055
HDD-36-15-S	36"	91¾"	601/2"	1,500	966
HDD-48-15-S	48"	1121/4"	721/2"	1,500	1029
HDD-60-15-S	60"	132¾"	841/2"	1,500	1134
HDD-72-15-S	72"	153"	96"	1,500	1186

STANDARD POWER IS 120V 1 PHASE AC

OPTIONAL 12V DC POWER WITH ON-BOARD CHARGER, MODEL HDD-DC OPTIONAL 5 GALLON PAIL ADAPTOR AVAILABLE, CONTACT FACTORY

UPGRADE TO STAINLESS STEEL CHUTE (must be ordered with above drum dumpers)							
CAPACITY 750 POUNDS	CAPACITY 1,000 POUNDS	CAPACITY 1,500 POUNDS					
MODEL Number	MODEL Number	MODEL Number					
SSC-36-7	SSC-36-10	SSC-36-15					
SSC-48-7	SSC-48-10	SSC-48-15					
SSC-60-7	SSC-60-10	SSC-60-15					
SSC-72-7	SSC-72-10	SSC-72-15					

## Lift-and-Dump Hydraulic Drum Dumpers

The Lift-and-Dump Hydraulic Drum Dumper is what you need to dump drums at variable heights. The HLD works similarly to the HDD but includes a lift cylinder that allows you to dump at various heights. Features a (4) push button pendant which allows the operator full independent control of both lift height and the dump angle. 120V 1-phase power standard.

PORTABLE LIFT A	ND DUMP DRUM	DUMPERS (40°	DUMP ANGL	Ε)			
MODEL Number	DUMP HEIGHT (MIN / MAX)	ROTATION Height	LEVEL HEIGHT	CAPACITY (POUNDS)	FRAME (W x L)	NET WT. (POUNDS)	
HLD-94-10-P	48" / 94"	166"	87"	1,000	44" x 69"	1372	
HLD-116-10-P	60" / 116"	195"	87"	1,000	44" x 77"	1460	
HLD-94-15-P	48" / 94"	166"	87"	1,500	44" x 69"	1392	
HLD-116-15-P	60" / 116"	195"	87"	1,500	44" x 77"	1480	
STATIONARY LIFT AND DUMP DRUM DUMPERS (45° DUMP ANGLE)							
HLD-94-10-S	48" / 94"	165"	86"	1,000	44" x 58"	1434	
HLD-116-10-S	60" / 116"	194"	86"	1,000	44" x 66"	1522	
HLD-94-15-S	48" / 94"	165"	86"	1,500	44" x 58"	1454	
HLD-116-15-S	60" / 116"	194"	86"	1,500	44" x 66"	1542	



(135° TOTAL ROTATION)

## **SPECIALTY POLISHES AND FINISHES**

**Contact Factory for Pricing** 



SSC option includes a 304 Stainless Steel chute in Mill Finish. Chute includes Steel-It™ coating standard on any mild steel welded to back of chute. Adjustable height clamps are stainless steel. Frame is painted enamel blue.

This option must be ordered with a Hydraulic Drum Dumper.

