



## Ground Tilter

The Ground Tilter is the best product for tilting applications which require the use of a pallet truck for loading and unloading. Rotate containers up to 45° from floor level to provide better access to parts in containers. Platform includes a 17" high lip on tilt side. A removable positioning bar is provided for use with smaller containers. Designed with worker safety in mind, pinch point guards are provided on all four sides of the unit. 2HP, 208-230/460V motor standard, other voltages available. Remote power unit with a protective cover measures 24"W x 24"L x 8"H. Hand pendant control standard. Optional foot control available.

MODEL NUMBER	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	LEVEL HEIGHT	MAXIMUM TILT	POWER UNIT	NET WT. (POUNDS)
GLT-4000	48" x 50"	4,000	1/2"	45°	EXTERNAL	1315

FOOT CONTROL, MODEL GLT-FC

## Bench Top Tilters

Heavy-duty steel Bench Top Tilters tilt loads from 0° to 45° (3" lip). Easily attached to most industrial table tops, work benches, and mobile lift tables of sufficient load capacity and surface size. Unit slides back as it tilts to maintain the center of gravity over the frame. Manual units need to be adjusted only when unloaded. Linear Actuated units are equipped with a push-button hand pendant control, located on an 8 foot cord. Flat base plate with slotted holes for installation.



MODEL NUMBER	PLATFORM SIZE (W x L x H)	CAPACITY (POUNDS)	MAXIMUM TILT	OPERATION	NET WT. (POUNDS)
BTT-6-36	28" x 36" x 2"	600	15°, 30° & 45°	MANUAL	60
BTT-6-46	28" x 46" x 2"	600	15°, 30° & 45°	MANUAL	72
BTT-5-36	28" x 36" x 5"	500	0° TO 45°	LINEAR ACTUATED	84
BTT-5-46	28" x 46" x 5"	500	0° TO 45°	LINEAR ACTUATED	96
BTT-10-36	28" x 36" x 3"	1,000	0° TO 45°	LINEAR ACTUATED	96
BTT-10-46	28" x 46" x 3"	1,000	0° TO 45°	LINEAR ACTUATED	108

## Air Corner Tilters


The floor level airbag powered tilter provides ergonomic loading and unloading of bulk containers, gaylords, or crates. Pallet truck and fork truck accessible. Tilts up to 45°. Activated by a hand operated control lever or foot pedal. By adjusting the air regulator to a predetermined pressure, the air bag inflates tilting the container automatically as it is unloaded. As the container becomes lighter, it automatically tilts and the material shifts to the corner of the container where it can be easily removed by manual or mechanical means. The adjustable regulator is factory preset to begin rotating the container when the weight reaches approximately 900 lbs. Pressure is easily adjustable for the weight of your application.



MODEL NUMBER	DESCRIPTION	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	NET WT. (POUNDS)
AIR-THL	HAND LEVER OPERATION	44" x 44"	1,500	460
AIR-TFP	FOOT TREADLE OPERATION	44" x 44"	1,500	460
AIR-PVO	POWER VIBRATOR OPTION	--	--	30

## Electric/Hydraulic Corner Tilters

Reduce repetitive motion injuries and fatigue while making your job easier and faster. Designed to corner tilt pallets, crates, boxes, or baskets 30°. AC powered with 2HP motor, 208-230/460V 3 phase with a push button control, other voltages available. Built in fork tubes for easy portability with a fork truck.



MODEL NUMBER	PLATFORM SIZE (W x L x H)	CAPACITY (POUNDS)	MAXIMUM TILT	NET WT. (POUNDS)
EMC-4242-2	42" x 42" x 24"	2,000	30°	750
EMC-4242-4	42" x 42" x 24"	4,000	30°	800
EMC-4848-2	48" x 48" x 24"	2,000	30°	800
EMC-4848-4	48" x 48" x 24"	4,000	30°	850

FOOT CONTROL, MODEL EMC-FC

## Manual Tilt Master

Lift, tilt, and transport crates, boxes, and pallets with an open bottom. Designed to give the user an ergonomically correct position to reach loads easily without the need for bending down or excessively reaching over. Forks can be tilted to 90°. Rolls smoothly on 6" x 2" polyurethane swivel casters with brake and foot protectors. Width between forks is 9½". The overall fork width is 22". The individual fork width is 6½".



MODEL NUMBER	CAPACITY (POUNDS)	VERTICAL LIFT HEIGHT	LOWERED FORK HEIGHT	FORK LENGTH	OVERALL WIDTH	NET WT. (POUNDS)
TM-22-M	2,200	11¼"	3½"	31½"	25¼"	425