





DVD or VIDEO AVAILABLE



SKID ONLY



NO PALLET

APPLIES TO ALL PRODUCTS ON THIS PAGE

High Rise Lift Trucks

Ergonomic lift truck increases worker and machine efficiency and productivity. Reduces muscle fatigue and body injuries by bringing material closer to actual worker height. 12V DC power with on-board battery charger standard. Heavy loads can be lifted by electric hydraulic power and manually moved until auto brake engages at approximately 8". Push buttons to raise and lower lift are located on power unit. Key-operated ON/OFF control for better security is built into the power unit. Unit rolls smoothly on phenolic 3" x 8" rear swivel casters and 3" x 2" front guide wheels.

MODEL NUMBER	FORK SIZE (W x L)	SERVICE RANGE	CAPACITY (POUNDS)	OPERATION	NET WT. (POUNDS)
HIPM-2748	27" x 48"	3½" to 31"	2,500	DC BATTERY	530
HIPM-2048	20" x 48"	3½" to 31"	2,500	DC BATTERY	515

HIGH RISE LIFT TRUCK OPTIONS

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
HIPM-PLATE	SOLID PLATFORM TO FIT OVER FORKS	36
HIPM-FC	FOOT TREADLE AIR/HYDRAULIC OIL OPTION	24
HIPM-AC	24V HAND HELD CONTROL, 110V AC POWER OPTION	48
HIPM-PTDS	POWER TRACTION DRIVE SYSTEM (OVERALL WIDTH 40")	156
HIPM-BCI	BATTERY CHARGE INDICATOR GAUGE (DC UNITS ONLY)	1
HIPM-FLK	MANUAL FLOOR LOCK	15

Tote Lifters

Designed to lift open bottom skids, boxes, and baskets. Two operations available: hand pump and 12V DC power with rocker switch to raise or lower. Hand pump design features an ergonomic pump handle with two lifting speeds to accommodate for light or heavy loads. Side stabilizers provide balance to the unit when the load is lifted. Suffix "SS" stands for stainless steel units. Stainless steel units feature nylon wheels.



DVD or VIDEO AVAILABLE

HAND PUMP
L-220-HD & L-270-HD



12V DC POWERED
L-220-DC-HD &
L-270-DC-HD



STAINLESS STEEL
12V DC POWERED
L-270-DC-HD-SS

MODEL NUMBER	OPERATION	FORK SIZE (W x L)	SERVICE RANGE	CAPACITY (POUNDS)	NET WT. (POUNDS)
L-220-HD	HAND PUMP	20" x 43"	3½" to 31½"	3,000	320
L-270-HD	HAND PUMP	27" x 43"	3½" to 31½"	3,000	340
L-270-HD-SS	HAND PUMP	27" x 45"	3½" to 31½"	3,000	340
L-220-DC-HD	12V DC POWERED	20" x 45"	3½" to 31½"	3,000	253
L-270-DC-HD	12V DC POWERED	27" x 45"	3½" to 31½"	3,000	427
L-270-DC-HD-SS	12V DC POWERED	27" x 45"	3½" to 31½"	3,000	427

TOTE-LIFTER OPTIONS

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
BC	REMOTE BATTERY CHARGER	8
BC-OB	ON-BOARD BATTERY CHARGER	9
BCI	BATTERY CHARGE INDICATOR GAUGE	1
L-PLATE-20	SOLID PLATFORM TO FIT OVER FORKS (20" Wide Unit)	36
L-PLATE-27	SOLID PLATFORM TO FIT OVER FORKS (27" Wide Unit)	37


Tote-A-Loads

Designed to lift open bottom skids, boxes, and baskets. The manually operated lift is easy to operate. The foot pump operated lift travels approximately 1/2" per stroke. To lower unit simply squeeze the bicycle style grip located on the white push bar. The battery operated lift is ideal for positioning products at workstation height for increased productivity. The up/down lever control is conveniently located on power unit. DC powered units include on-board charger. Polyurethane swivel casters with brake are standard on all units.



DVD or VIDEO AVAILABLE

FOOT PUMP
model TAL-260-HD



12V DC POWERED
model TAL-260-DC

MODEL NUMBER	DESCRIPTION	FORK SIZE (W x L)	CAPACITY (POUNDS)	SERVICE RANGE	NET WT. (POUNDS)
TAL-220-HD	FOOT PUMP	21" x 43"	2,200	3½" to 33"	315
TAL-260-HD	FOOT PUMP	27" x 43"	2,200	3½" to 33"	336
TAL-220-DC	12V DC POWERED	21" x 43"	2,200	3½" to 33"	415
TAL-260-DC	12V DC POWERED	27" x 43"	2,200	3½" to 33"	440

TOTE-A-LOAD OPTIONS

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
BC	REMOTE BATTERY CHARGER	8
TAL-PLATE	SOLID PLATFORM TO FIT OVER FORKS	36