







HAND CRANK

## **Basket & Skid Stackers**

Transport open bottom pallets, skids, baskets, and crates with ease. Features an 18" horizontal load center and overall fork width of 26". Available in 12V DC power (with on-board charger), AC power or Air/Oil power. Move the unit around easily on its 8" x 3" swivel phenolic rear casters. Handle height is 36". Push buttons to raise and lower 12V DC lift are located on the power unit. Hand control on coil cord standard. Key-operated ON/OFF control for better security is built into the 12V DC power unit.

MODEL Number	CAPACITY (POUNDS)	DESCRIPTION	FORK SIZE (W x L)	SERVICE Range	NET WT. (POUNDS)
PMSS-50-DC	4,000	12V DC POWER	6" x 36"	31/2" to 50"	1058
PMSS-60-DC	4,000	12V DC POWER	6" x 36"	31/2" to 60"	1078
PMSS-50-AC	4,000	115V AC POWER	6" x 36"	31/2" to 50"	1078
PMSS-60-AC	4,000	115V AC POWER	6" x 36"	31/2" to 60"	1078
PMSS-50-AIR	4,000	AIR/OIL POWER	6" x 36"	3½" to 50"	1078
PMSS-60-AIR	4,000	AIR/OIL POWER	6" x 36"	31/2" to 60"	1078

## Hydraulic and Winch Stackers


Safe ergonomic alternative to fork trucks at a fraction of the cost. Engineered for smooth operation and outstanding durability, the Hydraulic Stackers handle the following applications: lift and transport skids, bales, and baskets; load/unload trucks, stock shelves, handle dies, molds, or pallets. By combining a power lift with an easy to operate manual push, these Hydraulic Stackers are perfect for maneuvering in tight or congested areas. Complete with onboard charger. Features: 24" horizontal load center, adjustable straddle legs (34" to 50" I.D.), and adjustable forks 6" to 24" (O.D.). 6" swivel phenolic rear casters and 4" phenolic front wheels are standard.

The Compact Winch Stacker is a less expensive ergonomic alternative for lifting pallets of all sizes. This compact unit is perfect for loading/unloading trucks where docks are not available. Features include: safety cage, adjustable straddle legs (34" to 50" I.D.), winch with an automatic braking system, a floor brake to secure unit in place, adjustable forks (6" to 24" O.D.) and 4" swivel phenolic casters/4" phenolic front wheels.

MODEL NUMBER	OPERATION	SERVICE Range	CAPACITY (POUNDS)	OVERALL SIZE (W x L x H)	NET WT. (POUNDS)
HYS-60	12V DC POWERED	3" to 60"	1,500	40"-56" x 58" x 70"	688
HYS-96	12V DC POWERED	3" to 96"	1,500	40"-56" x 58" x 69"	855
HYS-144	12V DC POWERED	3" to 144"	1,500	40"-56" x 65" x 931/2"	925
CWS-60	HAND WINCH	3" to 60"	750	40"-56" x 50" x 70"	408

## Manual Work Positioners

These lightweight lifts are designed to take the strain out of any lifting job. Ideal for use in narrow aisles and confined spaces. Platform height is adjustable with a manual hand winch.



An auto brake system allows for controlled lowering. Quick change attachments available - contact factory for details.

MODEL Number	PLATFORM Size (W x L)			NET WT. (POUNDS)
MWP-220	181/2" x 231/2"	51/4" to 59"	220	105
MWP-440	18½" x 23½"	51/4" to 59"	440	155
MWP-VBLK		17		
MWP-RR	REEL ROTATOR ATTACHMENT			
MWP-DSPIN	DOUBLE SPINDLE ATTACHMENT			
MWP-SPIN		7		

## Versatile Quicklifts

An economical alternative DC powered lift. Ideal for light industrial or commercial applications. Features durable belt over pulley design. This lifter has a high service range and four swivel casters to provide great versatility and convenience. White high density (HDPE) plastic platform is scratch resistant, easy to clean, and retains an attractive appearance. Just 18 seconds for the 57" platform travel. Top wheels facilitate loading into a pick-up or van. Tool tray and remote battery charger is standard.

MODEL Number	PLATFORM Size (W x L)	CAPACITY (POUNDS)	SERVICE Range	OVERALL SIZE (W x L x H)	CASTERS FRONT/BACK	NET WT. (LBS.)
PEL-33	20½" x 18"	330	5-1/8" to 62"	20½" x 33" x 73½	3" / 4"	128
PEL-S	SINGLE SPINDLE				7	
PEL-DS	DOUBLE SPINDLE				11	