




WIRE MESH FOR HANDRAIL series WM



CONNECTION TUBING series CSEC



PLASTIC BUMPER model M-BUMP



60" SLIDING GATE model S-GATE-60



CORNER CONNECTORS model C-CON



CONCRETE ANCHOR BOLTS model VDKR-KIT

PROTECTIVE BARRIERS

Steel Square Safety Handrails

An economical way to protect people and machinery. Applications include loading docks, floor openings, walkways, and mezzanines. Highly visible safety yellow powder coat finish. Available with or without toeboards as application requires.

MODEL NUMBER	SQUARE TUBE (O.D.)	OVERALL HEIGHT	MIDRAIL HEIGHT	LENGTH	NET WT. (POUNDS)
RIGID SECTION WITH TOEBOARD					
SQ-48-TB	1-5/8"	42"	21"	48"	59
SQ-60-TB	1-5/8"	42"	21"	60"	64
SQ-72-TB	1-5/8"	42"	21"	72"	67
SQ-84-TB	1-5/8"	42"	21"	84"	72
SQ-96-TB	1-5/8"	42"	21"	96"	76
SQ-108-TB	1-5/8"	42"	21"	108"	80
SQ-120-TB	1-5/8"	42"	21"	120"	84
RIGID SECTION WITHOUT TOEBOARD					
SQ-48	1-5/8"	42"	21"	48"	42
SQ-60	1-5/8"	42"	21"	60"	48
SQ-72	1-5/8"	42"	21"	72"	50
SQ-84	1-5/8"	42"	21"	84"	55
SQ-96	1-5/8"	42"	21"	96"	60
SQ-108	1-5/8"	42"	21"	108"	66
SQ-120	1-5/8"	42"	21"	120"	70
OPTIONAL WIRE MESH					
WM-48	--	22"	--	48"	18
WM-60	--	22"	--	60"	25
WM-72	--	22"	--	72"	28
WM-84	--	22"	--	84"	32
WM-96	--	22"	--	96"	36
WM-108	--	22"	--	108"	41
WM-120	--	22"	--	120"	43
OPTIONAL CONNECTION TUBING (†)					
CSEC-48	1-5/8"	--	--	48"	14/PR.
CSEC-60	1-5/8"	--	--	60"	16/PR.
CSEC-72	1-5/8"	--	--	72"	18/PR.
CSEC-84	1-5/8"	--	--	84"	20/PR.
CSEC-96	1-5/8"	--	--	96"	22/PR.
CSEC-108	1-5/8"	--	--	108"	24/PR.
CSEC-120	1-5/8"	--	--	120"	25/PR.
OPTIONAL 4" HIGH TOEBOARD					
TOE-B-48	--	4"	--	43½"	17
TOE-B-60	--	4"	--	55½"	21
TOE-B-72	--	4"	--	67½"	25
TOE-B-84	--	4"	--	79½"	30
TOE-B-96	--	4"	--	91½"	34
TOE-B-108	--	4"	--	99"	36
TOE-B-120*	--	4"	--	111"	42
OPTIONS					
C-CON	CORNER CONNECTORS				10
S-GATE-60	60" SLIDING GATE				22
M-BUMP	72"L x 10"H BUMPER (HARDWARE INCLUDED)				43
VDKR-KIT	CONCRETE ANCHOR BOLTS (4) 3/8" x 3"				4

(†) CONNECTION TUBING IS PRICED & SOLD IN PAIRS

*RECEIVE (2) PIECES 55½" LONG EACH

Self-Closing Steel Gates

Customize your safety railings with Self-Closing Steel Gates. Gates can be mounted from the left or right with the included mounting hardware. Mount to horizontal rails that measure up to 2" diameter and are spaced 10" to 21" apart center to center. Choose from galvanized or yellow powder coat finish. Meets OSHA 1910.23a requirements. (Railing and base not included.)

MODEL NUMBER	MATERIAL	OPENING WIDTH	HEIGHT	NET WT. (POUNDS)
SPG-26-Y	YELLOW	16" to 26"	12"	30
SPG-26-G	GALVANIZED	16" to 26"	12"	30
SPG-40-Y	YELLOW	24" to 40"	12"	35
SPG-40-G	GALVANIZED	24" to 40"	12"	35

