

Low Profile Electric/Hydraulic Scissor Lift Tables


Load and unload skids with a pallet truck without the need for a pit when using the optional approach ramp. Superior engineering features rugged dependability. Safety features include electric perimeter pinch point guard, emergency stop velocity fuse in cylinders, fused 24V AC hand held control and maintenance supports. Remote power unit comes complete with a plastic cover to protect motor from dust and debris. Note motor voltage and phase when ordering.



Model Number Format EHLTX - (width)(length) - capacity - raised height

VERTICAL TRAVEL	PLATFORM WIDTH	PLATFORM LENGTH	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	TRAVEL TIME (SEC)	NET WT. (POUNDS)
35¾"	36" - 60"	53" - 60"	1,000	39"	3¼"	14	1470
35¾"	36" - 60"	53" - 60"	2,000	39"	3¼"	14	1627
35¾"	36" - 60"	53" - 60"	3,000	39"	4¼"	22	1680
35¾"	36" - 60"	53" - 60"	3,500	39"	4¼"	22	1869

APPROACH RAMPS FOR LOW PROFILE SCISSOR TABLES				
MODEL NUMBER	WIDTH	LENGTH	HEIGHT	NET WT. (POUNDS)
ARX-3617-3	36"	17"	3¼"	108
ARX-3623-3	36"	23"	3¼"	186
ARX-3622-4	36"	22"	4¼"	138
ARX-3630-4	36"	30"	4¼"	206



Low Profile "U" Type Electric Lift Tables

The open center on the "U" Type Electric Lift Tables enables a pallet truck to place a load on the platform. Units feature an external power pack equipped with a pressure relief valve that prevents overloading and a flow control valve that controls the lowering speed. Remote power pack comes complete with steel cover to protect the motor from dust and debris. Raise and lower the unit using the UP and DOWN push-buttons on the 24V control box. Safety features include electric toe guards, velocity fuse in cylinders, safety maintenance props and an emergency stop button on the control box.

MODEL NUMBER	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	LOWERED HEIGHT	RAISED HEIGHT	NET WT. (POUNDS)
EHU-2	45" x 56"	2,000	3-3/8"	33-7/8"	630
EHU-3	45¾" x 63"	3,000	4-1/8"	33-7/8"	850



Lift & Tilt Scissor Tables

Performs both lifting and tilting operations. 45° tilt standard. Restraining chain and 12" high lip to keep the load in place during tilting. Safety features include: electric toe guard to protect worker from pinch points during lowering of table, velocity fuses to stop travel due to loss of hydraulic pressure, 4 push-button hand pendant control on an 8 foot coil cord, upper limit switch to stop travel at maximum height reducing motor wear, and maintenance prop. End tilt standard, side tilt available. Optional accordion skirting available for both the lifting and tilting portions of the table, contact factory.

MODEL NUMBER	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	OVERALL SIZE (W x L)	NET WT. (POUNDS)
EHLTT-3648-1-47	36" x 48"	1,000	47"	11"	36" x 53"	1060
EHLTT-4848-1-47	48" x 48"	1,000	47"	11"	48" x 53"	1113
EHLTT-3648-2-47	36" x 48"	2,000	47"	11"	36" x 53"	1181
EHLTT-4848-2-47	48" x 48"	2,000	47"	11"	48" x 53"	1296
EHLTT-3648-3-47	36" x 48"	3,000	47"	11"	36" x 53"	1249
EHLTT-4848-3-47	48" x 48"	3,000	47"	11"	48" x 53"	1365
EHLTT-3648-4-47	36" x 48"	4,000	47"	11"	36" x 53"	1312
EHLTT-4848-4-47	48" x 48"	4,000	47"	11"	48" x 53"	1433

LIFT & TILT SCISSOR TABLE OPTIONS		
MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
EHLTT-FCH	FOUR PEDAL FOOT CONTROL (LIFT & TILT PRODUCTS)	12
EHLTT-HCA	AIR/OIL POWER W/PNEUMATIC PUSH BUTTON (FRL REQ'D)*	36

*FILTER - REGULATOR - LUBRICATOR REQUIRED TO OPERATE UNIT

