



Eco-COTE COATING

11-10

COLORS

11-10	White
11-11	Gray
11-13	Green
11-15	Blue
11-17	Yellow
11-18	Black
11-19	Red

SERVICE TEMPERATURE

-20 to 180°F
(-29 to 82°C)

COVERAGE

50 to 100 sq. ft./gal.

The coverage rate is dependent on the surface being covered and the application method used.

WEIGHT PER GALLON

11.1 lb.

AVERAGE NONVOLATILE

45% by weight
44% by volume

DRYING TIME

Touch: 2 hrs.

Through: 6 hrs.

The drying time depends on the temperature, humidity, and film thickness.

SAFETY

Flammability:

Wet: Non-Flammable.

Dry: Self-Extinguishing.

CAUTION:

Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not take internally. In an emergency, call a physician. Keep out of reach of children.

DESCRIPTION

Eco-Cote is water based, fire-resistive coating suitable for interior and exterior applications. It is ideal for color coding insulated pipes and vessels. Eco-Coat is compatible with 11-02 Eco-Perm Coating, 11-30 Eco-Lag Adhesive, 33-01 A.B. Mastic and 55-50 Eco-Mastic.

LIMITATIONS

Keep from freezing

Apply between 40°F (4°C) and 110°F (43°C).

MATERIAL PREPARATION

Stir well before using.

APPLICATION

This product is for industrial use only. It should be applied by trained and qualified craftspeople. Apply to clean oil-free surfaces. Apply a full even coat by brush, spray, or roller to previously lagged and sealed surfaces at a coverage rate of 75 sq. ft./gal.

CLEANUP

Fresh, clean water.

ASBESTOS FREE

Warranty Terms: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change without notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

Mon-Eco Industries, Inc.

5 Joanna Court • 800-899-6326 • East Brunswick, NJ 08816 732 257-7942 Fax: 732-257-6525