



ECO-FLEXIBLE INSULATION COATING 11-50

COLOR

White

WEIGHT PER GALLON

10.0 lbs.

SERVICE TEMPERATURE

-20°F to 180°F

COVERAGE

75 to 100 sq.ft./gallon

AVERAGE NONVOLATILE

45%

DRYING TIME

Touch: 1 Hour

Through: 24 Hours

SAFETY

Wet: Non-Flammable

Dry: Fire Resistive

CAUTION

Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor.

Avoid prolonged or repeated contact with skin.

Do not take internally. In an emergency, call a physician. Keep out of reach of children.

DESCRIPTION

Eco-Flexible Insulation Coating **11-50** is a tough, flexible, water-based coating designed for finishing closed cell rubber insulations. This coating applies easily and dries to an attractive, white low gloss, tightly adhered finish.

LIMITATIONS

Keep from freezing.

Apply between 40°F and 110° F.

APPLICATION METHOD

Brush, spray, roller

MATERIAL PREPARATION

Do not thin.

Stir well.

APPLICATION

This product is designed for industrial use only. It should be applied by trained and qualified craftspeople.

Apply to a clean, dust and oil free surface. Apply a smooth, even coat of **11-50** to the insulation to be coated. Do not over brush

CLEAN UP

Fresh, clean water

02/07

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. **WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE.** No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

MON-ECO INDUSTRIES, INC.

5 JOANNA COURT • EAST BRUNSWICK, NJ 08816
(732) 257-7942 • 800-899-6326 • FAX (732) 257-6525

www.mon-ecoindustries.com

