



Model Number	Control4® 5.25" In-Ceiling Speakers C4-IC5.25P	Control4® 6.5" In-Ceiling Speakers C4-IC6.5P	Control4® 8.0" In-Ceiling Speakers C4-IC8P	Control4® 6.5" In- Ceiling Stereo Speakers C4-SIC6.5S	Control4® 8.0" In- Ceiling Stereo Speakers C4-SIC8S	Control4® 6.5" In-Wall Speakers C4-IW6.5P	Control4® 8.0" In-Wall Speakers C4-IW8P
<b>Woofer</b>							
Infinite Baffle	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Voice Coil	1"	1"	1"	1"	1"	1"	1"
Kapton(r) VC & Former	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Polymer Cone	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Tweeter</b>							
Swivel Silk Soft Dome	3/4"	1"	1"	N/A	N/A	1"	1"
Neodymium Magnet Drive	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Liquid Cooled	Yes	Yes	Yes	No	No	Yes	Yes
<b>Specs</b>							
Frequency Response	58 Hz - 20 kHz +/- 3 dB	58 Hz - 20 kHz +/- 3 dB	48 Hz - 20 kHz +/- 3 dB	58 Hz - 20 kHz +/- 3dB	48 Hz - 20 kHz +/- 3 dB	58 Hz - 20 kHz +/- 3 dB	48 Hz - 20 kHz +/- 3 dB
Sensitivity	87 dB/1m/w	88 dB/1m/w	88 dB/1m/w	88 dB/1m/w	88 dB/1m/w	88 dB/1m/w	88 dB/1m/w
Minimum Required Power	10 W	15 W	15 W	15 W	15 W	15 W	15 W
Maximum Required Power	60 W	80 W	100 W	80 W	100 W	80 W	100 W
Nominal Impedance	8 ohms	8 ohms	8 ohms	8 ohms	8 ohms	8 ohms	8 ohms
Cutout Dimensions	6.44" diameter	7.38" diameter	8.63" diameter	7.38" diameter	8.63" diameter	10.25" H x 7.25" W	12.75" H x 8.69" W
Mounted Dimensions	8" diameter	8.5" diameter	9.88" diameter	8.5" diameter	9.88" diameter	12" H x 8.5" W	14.13" H x 10" W
<b>Engineering Features</b>							
Open-Slope Composite Filter Engineering	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Field-Replaceable Tweeter	Yes	N/A	N/A	N/A	N/A	N/A	N/A
Gold-Plated Binding Posts	No	Yes	Yes	Yes	Yes	Yes	Yes
Speaker Wire Gauge Accepted	Up to 16 gauge	Up to 14 gauge	Up to 14 gauge	Up to 14 gauge	Up to 14 gauge	Up to 14 gauge	Up to 14 gauge
<b>Mounting</b>							
One-Piece Design	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Screw-Foot Pull-Down	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Paintable	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Grill and Mounting Hardware Included	Yes	Yes	Yes	Yes	Yes	Yes	Yes