



# Sheetrock® Brand Lay-In Ceiling Panel *CLIMAPlus*™



Fine textured panel

## Features and Benefits

- Panels meet U. S. Dept. of Agriculture Food Safety Inspection Service requirements for food processing areas.
- *CLIMAPlus*™ 15-year System Warranty to withstand temperature and humidity conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with USG's *DONN*® Brand Suspension Systems.
- *SHEETROCK*® Brand Lay-In Ceiling Panel, *CLEAN ROOM*™ have a gypsum core, sealed edges, and a vinyl face and back; they meet USDA/FSIS requirements for food processing and can be used in clean room environments up to Class 100.
- *FIRECODE*™ formulation designed to meet life safety codes.

## Applications

- Exterior soffits
- Parking garages
- Kitchens and food preparation areas
- Restrooms and utility areas
- Locker rooms
- Marine environments

# Sheetrock® Brand Lay-In Ceiling Panel *ClimaPlus*™

Acoustical Ceilings

Technical Service 800 USG.4YOU  
Web Site [www.usg.com](http://www.usg.com)  
Samples/Literature 888 874.2450  
Samples/Literature Fax 888 874.2348  
Customer Service 800 950.3839  
Literature Number SC1820



	Edge	Panel Size	Class	Item No.	NRC <sup>1</sup>	CAC Min.	LR <sup>2</sup>	Color	Grid Options	Recycled Content <sup>3</sup>	Panel Cost
SHEETROCK® Brand Lay-In Ceiling Panel <i>CLIMAPLUS</i> ™, Vinyl	(SQ)	2' x2' x1/2"		3260	—	35	.77	White	A, B, C, D,	23%	\$
		2' x4' x1/2"		3270	—	40	.77	White	A, B, C, D,	23%	\$
SHEETROCK Brand Lay-In Ceiling Panel <i>CLIMAPLUS</i> , CLEAN ROOM™	(SQ)	2' x4' x1/2"		3200	—	40	.77	White	A, B, C, D,	23%	\$\$
	<b>A</b> DONN® DX®/ DXL™	<b>B</b> DONN DXLA™	<b>C</b> ZXLA™	<b>D</b> DONN CE <sup>5</sup>							
<b>Grid Profile Options<sup>4</sup></b>											

**ASTM E1264 classification**

Type XX, Pattern G

**ASTM E84 surface burning characteristics**

Class A

Vinyl

Flame spread: 20

Smoke developed: 5

CLEAN ROOM

Flame spread: 20

Smoke developed: 5

**Weight**

1/2" = 2.00 lb./ft<sup>2</sup>

**Thermal resistance**

1/2" = up to R-0.45

**Maximum backloading**

See Warranty for details.

**Maintenance**

Can be cleaned easily with a damp sponge. Use mild detergent and water – do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

**Humidity resistance**

Tested by 48-hour cycles of 90% and 25% relative humidity repeated continuously for 24 days with no delamination.

**U.S. Coast Guard acceptance**

Approved for use on merchant ships.

**Footnotes**

1. NRC rating is .10. USG does not consider a ceiling panel to be acoustically rated if NRC is less than .50
2. LR values are shown as averages.
3. For details, see the Recycled Content selector.
4. Field-cut edges of CLEAN ROOM panels must be sealed with white latex paint, shellac, or a mixture of 50% water and 50% water-soluble glue.
5. Clean-room-rated applications require a suspension system with gasketed tee flanges such as DONN CE.

**SAFETY FIRST!**

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by  
USG Interiors, Inc.  
125 South Franklin Street  
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company:  
CLIMAPLUS, DONN, DX, DXL, DXLA, FIRECODE, SHEETROCK, USG, ZXLA.

SC1820/6-04  
© 2004, USG Interiors, Inc.  
Printed in U.S.A.