



PANZ Metal Ceiling Panels (FL edge) in Flat White/  
DONN CENTRICITEE DXT Suspension System

### LEED Credits

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials <sup>1</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance <sup>2</sup>
●	●	●				●

### Features and Benefits

- Simple lay-in design provides 100% access.
- ACOUSTIBOND® sound backer produces .65 NRC without additional acoustical material when panels are installed within an enclosed plenum (minimum plenum depth: 18”).
- Available in numerous perforation patterns.
- Creates reveal edge on field-cut panel.
- Available with same edge details as USG acoustical panels.

### Applications


- Computer and utility rooms
- Entertainment
- Gaming
- Frequently accessed plenums



### Call 888.874.2450 for color samples

See IC415 for color and perforation availability.


#### Diamondflex<sup>2</sup>



#### Painted Metals




#### Premium Metals



#### Wood Tones












#### Anodized Metals



	<b>Product Information</b>		
	<b>Materials</b>	<b>Typical Sizes</b>	<b>Finishes</b>
	Panels: Aluminum	2' x 2', 2' x 4', 4' x 4'	2' x 2' panels available with perforation and/or embossing.

<b>Acoustics</b>	<b>Description</b>	<b>Optional Acoustical Material</b>	<b>Sound Rating – NRC</b>	
			<b>Perforation A062</b>	<b>Perforation A116</b>
	Perforated panel	ACOUSTIBOND backer <sup>1</sup>	.65	.70
	Perforated panel	1-1/2", 6 lb. density fiberglass	.90	.95
	Perforated panel	2", .75 lb. fiberglass in poly bag	.85	.90

<b>Panels</b>	<b>Smooth Panel</b>	<b>Perforated Panel</b>	<b>Perforated Panel with ACOUSTIBOND<sup>3</sup> Backer</b>
			

<b>Edge Details</b>	<b>Square Edge with 15/16" DX®/DXL™ Suspension</b>	<b>Square Edge with 9/16" CENTRICITEE™ DXT Suspension</b>	<b>Shadowline Edge with 15/16" DX/DXL Suspension</b>	<b>Fineline Edge with 9/16" CENTRICITEE DXT Suspension</b>
				
	<b>Fineline Edge with 9/16" FINELINE® DXF Suspension</b>	<b>Fineline Edge with 9/16" FINELINE® 1/8 DXFF Suspension</b>		
				

**For More Information**

**Product literature**  
 System brochure: IC415  
 Data sheet: IC314  
  
**Online tools**  
 usgdesignstudio.com

**Light reflectance**  
 Flat White: LR-0.8  
 (less with perforations).  
  
**Recycled content**  
 PANZ aluminum panels: 70% recycled content.

**Footnote**  
 1. Dependent on location; contact your USG representative.  
 2. Requires perforation and ACOUSTIBOND backer.  
 3. ACOUSTIBOND backer not standard with DIAMONDFLEX panels.