

Panz® Planks and Large Sizes



600mm x 1050mm PANZ Field Panels, 400mm x 1800mm PANZ Channel Panels

LEED Credits

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials ¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance ²
●	●	●				●

Features and Benefits

- Range of sizes for large-module ceilings.
- Available in numerous painted colors and Wood Tones, and a range of perforation patterns.
- Simple lay-in design provides 100% access.
- Perforated panels with ACOUSTIBOND® sound backer produce .65 NRC without additional acoustical material (enclosed plenum, minimum depth 18”).
- Available with same edge details as USG acoustical panels.

Applications

- Computer and utility rooms
- Entertainment
- Gaming
- Frequently accessed plenums



Call 888.874.2450 for color samples

See IC415 for color and perforation availability.

Painted Metals



Flat White



Silver Satin
002



Metallic Copper
1690



Metallic Gold
1691



Metallic Oyster
1652

Wood Tones³












Cherry



Maple



Oak

	Product Information			
	Materials	Typical Sizes		
	Aluminum Panels	1' x 4', 1' x 5', 20" x 60", 2' x 6', 2' x 8', 30" x 60",		
Acoustics	Description	Optional Acoustical Material	Sound Rating – NRC	
			Perforation A062	Perforation A116
	Perforated panel	ACOUSTIBOND backer	.65	.70
	Perforated panel	1-1/2", 6 lb. density fiberglass	.90	.95
	Perforated panel	2", .75 lb. fiberglass in poly bag	.85	.90
Panels	Smooth Panel	Perforated Panel – ACOUSTIBOND Backer Standard	Perforated Panel (No Backer – Optional)	
				
Edge Details	Square Edge with 15/16" DX®/DXL™ Suspension	Square Edge with 9/16" CENTRICITEE™ DXT Suspension	Shadowline Edge with 15/16" DX/DXL Suspension	Fineline Edge with 9/16" CENTRICITEE DXT Suspension
				
	Fineline Edge with 9/16" FINELINE® DXF Suspension	Fineline Edge with 9/16" FINELINE® 1/8 DXFF Suspension		
				

For More Information

Product literature

System brochure: IC415
Data sheet: IC541

Online tools

– usgdesignstudio.com
– usg.planks.pivotinteractive.com

Light reflectance

Flat White: LR-0.8
(less with perforations).

Recycled content

PANZ aluminum panels:
70% recycled content.

Footnote

1. Dependent on location; contact your USG representative.
2. Requires perforation and ACOUSTIBOND backer.
3. Available for 1' x 4', 1' x 5', 20" x 60" and 2' x 6' panels.