



WireWorks Open-Cell Ceiling Panels, Weave Pattern/  
GridWare GWDX Suspension System in Silver Satin

### LEED Credits

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials <sup>1</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●				

### Features and Benefits

- Metal, woven lay-in panels with powder-coated finish are abuse resistant and highly durable.
- Four cell sizes offer flexibility to meet design and budget needs.
- Combine with the GridWare™ suspension system to create custom ceiling system.
- Easy installation into standard Down® brand suspension systems.
- Easily accommodates lightweight signage.
- Custom colors available.

### Applications

- Accent areas
- Educational
- Health care
- Retail stores

Call 888.874.2450 for color samples



















High-Gloss White



Chrome



		Product Information			
		Materials	Typical Sizes	Wire Thickness	
		Robotically welded steel wire.	2' x 2'	Panels are 1/8"; Forms are 3/16".	
WIREWORKS Ceiling Panels 2' x 2' 1/8" Wire		1" x 1" Cells	2" x 2" Cells	3" x 3" Cells	4" x 4" Cells
					
	WIREWORKS Forms 2' x 2' 3/16" Wire	Weave	Pattern	Front Profile	Side Profile
					
		Ripple	Pattern	Front Profile	Side Profile
					
	Small Wave	Pattern	Front Profile	Side Profile	
					
	Big Wave	Pattern	Front Profile	Side Profile	
					

**For More Information**

**Product literature**  
System brochure: IC34103  
Data sheet: IC325

**Online tools**  
usgdesignstudio.com

**Recycled content**  
Wireworks panels: 25% recycled content

**Metric equivalents**  
Contact Technical Service for additional information.

**Footnotes**  
1. Dependent on location; contact your USG representative.