

# Eclipse™ *ClimaPlus*™ Illusion and Pedestals



10

Year Availability  
78785



ECLIPSE Pedestals IV Panels with *CLIMAPLUS* Superior Performance/  
DONN CENTRICITEE DXT Suspension System

### LEED Credits

Recycled Content: 77%  
*CLIMAPLUS* Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction <sup>1</sup>	Recycled Content	Regional Materials <sup>2</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

### Features and Benefits

- A variety of face scores create the illusion of a smaller-scaled ceiling system without compromising accessibility.
- Solid NRC performance of up to .70 meets general office acoustical needs for sound absorption.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand temperature and humidity conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a Donn® brand suspension system.

### Applications

- Boutiques
- Schools
- Reception lobbies
- Transportation terminals

### Substrate

- X-Technology mineral fiber



Call 888.874.2450 for samples



White

**30**  
 Year System Warranty  
 - No visible sag  
 - Mold/mildew protection

UL Classified													
Edge	Panel Size	Class	Item No.	NRC	CAC Min. <sup>3</sup>	LR <sup>4</sup>	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>5</sup>	Panel Cost	
<b>ECLIPSE CLIMAPLUS Illusion Two/24 Panels</b> The look of 2'x2' panels	SLT <sup>6</sup> 	2'x4'x3/4"	Class A	<b>78785</b>	.70	35	.84	White	A	Low		77%	\$\$
	ILT <sup>7</sup> 	2'x4'x3/4"	Class A	<b>78085</b>	.70	35	.84	White	B	Low		77%	\$\$
<b>ECLIPSE CLIMAPLUS Pedestals I Panels</b> Triple-step scoring	PE/SLT 	2'x2'x3/4"	Class A	<b>72715</b>	.65	35	.84	White	C	Low		77%	\$\$
	PE/ILT 	2'x2'x3/4"	Class A	<b>72015</b>	.65	35	.84	White	D	Low		77%	\$\$
<b>ECLIPSE CLIMAPLUS Pedestals IV Panels</b> Triple-step scoring in 12"x12" modules	PE/SLT <sup>6</sup> 	2'x2'x3/4"	Class A	<b>72716</b>	.65	35	.84	White	C	Low		77%	\$\$
	PE/ILT <sup>7</sup> 	2'x2'x3/4"	Class A	<b>72215</b>	.65	35	.84	White	D	Low		77%	\$\$
<b>Patterns</b>	<b>Illusion Two/24</b> 		<b>Pedestals I</b> 		<b>Pedestals IV</b> 								
<b>Legend</b>													
<b>Low Emissions (VOC Class)</b> Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.				<b>CLIMAPLUS Superior Performance<sup>8</sup></b> Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold/mildew, fungi, yeast, algae, and Gram-positive and Gram-negative odor/stain-causing bacteria.									
<b>A</b> DX®/DXL™ 	<b>B</b> CENTRICITEE™ DXT 	<b>C</b> DX/DXL 	<b>D</b> CENTRICITEE DXT 										
<b>Grid Profile Options</b>													

**Physical Data/ Footnotes**

**Product literature**  
Data sheet: SC1846

**ASTM E1264 classification**  
Type III, Form 1, Pattern EIK (Illusion) or Pattern EI (Pedestals)

**ASTM E84 surface burning characteristics**  
Class A  
Flame spread: 25  
Smoke developed: 50

**Weight**  
.97-1.2 lb./sq. ft.

**Thermal resistance**  
R-2.0

**Maximum backloading**  
See Warranty for details.

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

**Patented technology**  
This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

**Footnotes**

1. Applies when USG acoustical ceilings recycling program is utilized.
2. Dependent on location; see Sustainability selector.
3. Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
4. LR values are shown as averages.
5. For details, see Sustainability selector.

6. Panels have a 15/16" routing.
7. Panels have a 9/16" routing.
8. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold/mildew, fungi, yeast, and odor/stain-causing Gram-positive and Gram-negative bacteria. For details, see *Ceiling Systems Warranties and Limitations (SC2102)* and *CLIMAPLUS Ceilings Certification of Performance (SC2451)*

**Note**  
Panels with face routing do not carry USG's CLIMAPLUS non-sag warranty. Refer to standard commercial ceilings warranty.