



WireWorks Open-Cell Ceiling Panels, Weave Pattern/  
GridWARE GWDX Suspension System in Silver Satin

### LEED Credits

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●				

### Features and Benefits

- Metal, woven lay-in panels with powder-coated finish are abuse resistant and highly durable.
- Four cell sizes offer flexibility to meet design and budget needs.
- Combine with the GridWARE™ suspension system to create custom ceiling system.
- Easy installation into standard Down® brand suspension systems.
- Easily accommodates lightweight signage.
- Custom colors available.

### Applications

- Accent areas
- Educational
- Health care
- Retail stores

Call 888.874.2450 for color samples



















High-Gloss White



Chrome



Product Information				
Materials		Typical Sizes	Wire Thickness	
Robotically welded steel wire.		2' x 2'	Panels are 1/8"; Forms are 3/16".	
<b>WIREWORKS Ceiling Panels</b> 2' x 2' 1/8" Wire	<b>1" x 1" Cells</b>	<b>2" x 2" Cells</b>	<b>3" x 3" Cells</b>	<b>4" x 4" Cells</b>
				
	<b>Weave</b>	<b>Pattern</b>	<b>Front Profile</b>	<b>Side Profile</b>
				
<b>Ripple</b>				
<b>Small Wave</b>				
<b>Big Wave</b>				

**For More Information**

**Product literature**  
 System brochure: IC34103  
 Data sheet: IC325  
**Online tools**  
 usgdesignstudio.com

**Recycled content**  
 Wireworks panels: 25% recycled content  
**Metric equivalents**  
 Contact Technical Service for additional information.

**Footnotes**  
 1. Dependent on location; contact your USG representative.