

Sheetrock® Lay-In Ceiling Panel *ClimaPlus*, PVC-FREE



SHEETROCK Lay-In Ceiling Panel with *CLIMAPLUS* Performance/
DONN ZXLA Suspension System

LEED Credits

Recycled Content: 56%
CLIMAPLUS No-Sag Warranty

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials ¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	●	●	●	●	●	●

Features and Benefits

- Proprietary non-vinyl face material is free of PVC and Phthalates
- High UV resistance helps resist color change over time
- Washable and Scrubbable finish—Impact, Scratch and Soil Resistant
- Panels meet USDA/FSIS requirements for food processing areas
- *CLIMAPLUS*™ 30-year lifetime no-sag system warranty

Applications

- Kitchens and food preparation areas
- Restrooms and utility areas
- Locker rooms
- Parking garages
- Exterior protected soffits

Substrate

- Gypsum panel

Call 888.874.2450 for color samples



White

Smooth-textured panel — PVC-FREE



Sheetrock® Lay-In Ceiling Panel *ClimaPlus*™, PVC-FREE

Web Sites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

Technical Service 800 USG.4YOU
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839

See usg.com for
the most up-to-date
product information.

UL Classified												
Edge	Panel Size	Class ²	Item No.	NRC ³	CAC Min.	LR ⁴	Color	Abuse-Resistant	Grid Options	Recycled Content ⁵	Panel Cost	
30 Year System Warranty – No visible sag												
SHEETROCK Lay-In Ceiling Panel <i>CLIMAPlus</i>, PVC-FREE	SQ 	2'x2'x1/2"		3220	—	35	.85	White		A, B, C, D	56%	\$
		2'x4'x1/2"		3230	—	40	.85	White		A, B, C, D	56%	\$
Grid Profile Options	A DONN® DX®/DXL™ 	B DONN® DXLA™ 	C ZXLA™ 	D DONN CE™ 								

Physical Data/ Footnotes

Product literature
Data sheet: SC2504

ASTM E1264 classification
Type XX, Pattern G

ASTM E84 surface burning characteristics
Class A
PVC-FREE
Flame spread: 25
Smoke developed: 50

Weight
1/2" = 2.00 lb./sq. ft.

Thermal resistance
1/2" = up to R-0.45

Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a damp sponge. Use mild detergent and water – do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

Footnotes

1. Dependent on location; see Sustainability selector.
2. Fire-rated items: see UL design details.
3. NRC rating is .10. USG does not consider a ceiling panel to be acoustically rated if NRC is less than .50
4. LR values are shown as averages.
5. For details, see Sustainability selector.

6. High Scrubbability/High Washability—PVC-FREE panels have been tested to withstand 10,000 scrub/wash cycles (ASTM D2486/ASTM D4828)



Manufactured by USG Interiors, Inc.
550 West Adams Street
Chicago, IL 60661

The following are trademarks of USG Interiors, Inc. or a related company: CE, *CLIMAPlus*, DONN, DX, DXL, DXLA, FIRECODE, SHEETROCK, USG, ZXLA.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC2504/rev. 10-09
© 2009, USG Interiors, Inc.
Printed in U.S.A.