



Eclipse[™] *ClimaPlus*[™] Illusions and Pedestals



Fine textured panel



ECLIPSE *CLIMAPLUS* Illusion Two/24 Panels/CENTRICITEE Suspension



Features and Benefits

- A variety of face scores create the illusion of a smaller-scaled ceiling system without compromising accessibility.
- Solid NRC performance of .70 meets general office acoustical needs for sound absorption.
- *CLIMAPLUS*[™] 30-year Lifetime System Warranty to withstand temperature and humidity conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with USG's *DONN*[®] Brand Suspension Systems.
- Panel used in *RENDITIONS*[™] Face-Routed Ceiling Systems (see IC327).

Applications

- Boutiques
- Schools
- Reception lobbies
- Transportation terminals

Eclipse™ *ClimaPlus*™ Illusion and Pedestals

Acoustical Ceilings

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC1846



UL Classified

	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost
ECLIPSE™ CLIMAPLUS™ Illusion Two/24 Panels The look of 2'x2' panels	(SLT) ³ 	2' x4' x3/4"	Class A	78785	.70 	35	.84	White	A	78%	\$\$
	(ILT) ⁴ 	2' x4' x3/4"	Class A	78085	.70 	35	.84	White	B	78%	\$\$
ECLIPSE™ CLIMAPLUS™ Pedestals I Panels Triple-step scoring	(PE/SLT) 	2' x2' x3/4"	Class A	72715	.70 	35	.84	White	C	78%	\$\$
	(PE/ILT) 	2' x2' x3/4"	Class A	72015	.70 	35	.84	White	D	78%	\$\$
ECLIPSE™ CLIMAPLUS™ Pedestals IV Panels Triple-step scoring in 12"x12" modules	(PE/SLT) ³ 	2' x2' x3/4"	Class A	72716	.70 	35	.84	White	C	78%	\$\$
	(PE/ILT) ⁴ 	2' x2' x3/4"	Class A	72215	.70 	35	.84	White	D	78%	\$\$
	Illusion Two/24		Pedestals I		Pedestals IV		RENDITIONS™⁵				
Patterns											
	A DONN® DX®/ DXL™	B CENTRICITEE™	C DONN DX/DXL	D CENTRICITEE							
Grid Profile Options											

ASTM E1264 classification
Type III, Form 1 or 2, Pattern EIK (Illusion) or Pattern EI (Pedestals)
ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 25
Weight
1.04 lb./ft.²

Thermal resistance
R-2.6
Maximum backloading
See Warranty for details.
Maintenance
Can be cleaned easily with a soft brush or vacuum.

Patented technology
This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

Footnotes
1. LR values are shown as averages.
2. For details, see the Recycled Content selector.
3. Panels have a 15/16" routing.
4. Panels have a 9/16" routing.
5. See RENDITIONS Face-Routed Ceiling Panels (IC327) in USG Specialty Ceilings binder for more information.

SAFETY FIRST!
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company: CENTRICITEE, CLIMAPLUS, DONN, DX, DXL, ECLIPSE, RENDITIONS, USG.

SC1846/rev. 6-04
© 2004, USG Interiors, Inc.
Printed in U.S.A.