






RADAR™ Illusion Two/24 Panels/Donn® Brand DX®/DXL™ Suspension System



Features and Benefits

- Non-directional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern in many sizes.
- A variety of face scores create the illusion of a smaller-scaled ceiling without compromising accessibility.
- Optional Firecode[™] formulation designed to meet life safety codes.
- Illusion Two/24 panel edges and center score painted for sharp, clean appearance.

Applications

- Executive and administrative areas
- Grocery stores
- Hotels
- Offices
- Restaurants

Acoustical Ceilings

Radar[™] Illusion

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC2289

					(A) UL	Classified					
	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	
RADAR™ Illusion Two/24 Panels The look of 2'x2' panels	(SLT) ³	2′x4′x3/4″	Class A	2742	.55	35	.82	White	A	25%	\$\$
Z XZ pariolo	Illusion Two/24										
Pattern											
	A Donn® DX®/ DXL™										
Grid Profile Options		5									
	Panel edges and center score nainted for sharn clean annearance										

ASTM E1264 classification Type III, Form 2, Pattern CDK ASTM E84 surface burning characteristics

Class A Flame spread: 25 Smoke developed: 10 Weight 1.06 lb./ft.² Thermal resistance R-1.7 **Maximum backloading** See Warranty for details. **Maintenance** Can be cleaned easily with

Can be cleaned easily with a soft brush or vacuum.

Footnotes

- LR values ares shown as averages.
- 2. For details, see the Recycled Content selector.
- 3. Panels have 15/16" routing.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

