



## JOINT TREATMENT SYSTEMS

PRODUCT	PACKAGE SIZE	COVERAGE	STANDARDS ASTM
<b>DensArmor Cote™ All-Purpose Ready-Mix Joint Compound</b> Premium pre-mixed, ready-to-use compound for bedding tape, finishing joints and skim coating and texturing. Ideal for maximum mold resistance.	61.7 lb. pails	61.7 lbs. per 500 sq. ft.	C 475
<b>ToughRock® All-Purpose Dry Joint Compound</b> Use for bedding tape, finishing joints, filling corner bead, spotting, skim coating and texturing.	25 lb. bags	25 lbs. per 400 sq. ft. for joints; 75 lbs. per 1,000 sq. ft. for texturing	C 475
<b>ToughRock® Ready-Mix All-Purpose Joint Compound</b> Pre-mixed, ready to use for bedding tape, finishing joints and skim coating and texturing.	12 lb. pails 20 kg pails 61.7 lb. pails 28 kg pails 48 lb. ctn. 27 kg ctn.	61.7 lbs. per 500 sq. ft.	C 475
<b>ToughRock® Lightweight Joint Compound</b> Pre-mixed, ready to use for finishing joints and cornerbead. Shrinks less and is easier to sand than conventional All-Purpose.	17 liter cartons 4.5 gallon cartons 1 gallon pail	4.5 gallons per 500 sq. ft.	C 475
<b>ToughRock® Semi-Light Joint Compound</b> Pre-mixed, ready to use for bedding tape, finishing joints, cornerbead and skim coating.	23 kg cartons 3.5 & 4.5 gallon cartons and pails	4.5 gallons per 500 sq. ft.	C 475
<b>ToughRock® Setting Compounds</b> Use for all bedding and topcoats. Allows complete taping and finishing in one day. Recommended for cold weather and slow drying conditions. Hardens by setting, not drying. Available 45- and 90-minute. Ideal products for patch and repair jobs.	15 kg bags	50-60 lb. per 1,000 sq. ft. or 22-27 kg. per 100 sq. m.	C 475

**JOINT TREATMENT SYSTEMS (continued)**

PRODUCT	PACKAGE SIZE	COVERAGE	STANDARDS ASTM
<b>ToughRock® Sandable Setting Compounds</b> Same use as ToughRock® Setting Compounds. Applies and sands easier than ToughRock Setting Compounds. Available in 45- and 90-minute. Ideal products for patch and repair jobs.	18 lb. bags 11 kg bags	50-60 lb. per 1,000 sq. ft. or 22-27 kg. per 100 sq. m.	C 475
<b>ToughRock® Ready-Mix Topping Compound</b> Pre-mixed and ready to use. Finish applications only. Easy to sand.	61.7 lb. pails 48 lb. cartons	40 lbs. per 500 sq. ft.	C 475
<b>ToughRock® Fire-Halt® Sealant</b> A noncombustible fast-setting compound for use as a firestop sealant for penetrations such as pipes, conduit and telephone cables in fire-resistive assemblies; and as filler for the flutes in steel decks. Listed with Warnock Hersey International.	15 lb. pails 33 lb. bags	1 lb. powder mixed will fill approx. 30 cubic in.	C 475
<b>ToughRock™ Tape</b> Special 2 1/16" wide paper tape. Reinforces gypsum joints. Pre-creased for ease of application.	75 ft. rolls 250 ft. rolls 500 ft. rolls	400' per 1,000 sq. ft. of gypsum board	C 475

**TEXTURES AND VENEER PLASTERS**

<b>DensArmor Cote™ Interior Veneer Plaster</b> A one or two coat plaster designed for commercial & residential wall/ceiling applications. Abrasion, damage and mold resistant.	50 lb. bags	150 sq. ft. per bag	C 587
<b>PearlCote™ Interior Veneer Plaster</b> A one or two coat plaster designed for commercial & residential wall/ceiling applications. Abrasion, damage and mold resistant.	50 lb. bags	150 sq. ft. per bag	C 587
<b>ToughRock™ Ceiling Textures/Vermiculite</b> For spray applications only. As decorative finish on gypsum wallboard or concrete ceilings. Not recommended for high-moisture areas such as bathrooms.	40 lb. bags	varies from 300 to 400 sq. ft. per bag	
<b>ToughRock™ Regency Ceiling Textures/Polystyrene</b> For spray application only. A high-quality aggregate finish with superior ceiling coverage. For use with gypsum board or concrete ceilings. Not recommended for high-moisture areas such as bathrooms.	16 kg bags 40 lb. bags 50 lb. bags	250 sq. ft. per bag 285 sq. ft. per bag 350 sq. ft. per bag	
<b>ToughRock™ Wall and Ceiling Texture</b> A decorative spray application for both walls and ceilings. Commonly used for splatter application; knock-down and orange peel type textures.	50 lb. bags	up to 2,000 sq. ft. per bag approximately 400 sq. ft. per bag for other applications	

*Note: Some products are not available at all plants or locations. Call sales office listed for specific product availability.*



**SALES INFORMATION AND ORDER PLACEMENT**

U.S.A. Midwest: **1-800-876-4746** West: **1-800-824-7503**  
South: **1-800-327-2344** Northeast: **1-800-947-4497**

CANADA Canada Toll Free: **1-800-387-6823**  
Quebec Toll Free: **1-800-361-0486**

**TECHNICAL INFORMATION**

Georgia-Pacific Gypsum Technical Hotline  
U.S.A. and Canada: **1-800-225-6119**  
Mon.-Fri., 8 a.m.-5 p.m. ET  
www.gpgypsum.com

**TRADEMARKS** The Georgia-Pacific logo and all trademarks are owned by or licensed to Georgia-Pacific Gypsum LLC.

**UPDATES AND CURRENT INFORMATION** The information in this document may change without notice. Visit our Web site at [www.gpgypsum.com](http://www.gpgypsum.com) for updates and current information.

**LIMITATION OF REMEDIES AND DAMAGES** Unless otherwise stated in our written warranty for these products, our sole liability for any product claim shall be limited to reimbursement of the cost of repair or replacement of the affected product, up to a maximum amount of two times the original purchase price for the affected product. We shall not be responsible under any circumstances for lost profits, damage to a structure or its contents, or indirect, incidental, special or consequential damages. Claims shall be deemed waived if they are not submitted to us in writing within ten days after discovery.

**SAFETY CAUTION:** Some of these products contains fiberglass. Fibers and dust may be released from this product during normal handling and may result in skin, eye and respiratory irritation. Avoid breathing dust and contact with the skin and eyes. Follow these standard work practices: Wear a loose-fitting, long-sleeved shirt and long pants, protective gloves and eye protection (goggles or safety glasses with side shields). Wear a dust mask when sanding. Additional protection may be needed when very dusty. Do not use a power saw. For Material Safety Data Sheet or additional information, call 1-800-225-6119 or visit our Web site.