

# ProForm<sup>®</sup> BRAND Joint Tapes

ProForm BRAND Joint Tape is designed for use with ready mixed or setting type compounds to conceal and reinforce joints of interior walls and ceilings.

## ProForm<sup>®</sup> Paper Joint Tape

---



### Description

Conceals and reinforces wallboard joints. Tape is 2-1/6" wide and is buffed on both sides to ensure the best working qualities and bond. Center crease allows easy folding for use in corners. Can be used with all ProForm Ready Mix and Sta-Smooth Setting Compounds.

### Packaging

Available in:  
75' rolls (22.9 m)  
20 rolls per carton  
250' rolls (76.2 m)  
20 rolls per carton  
500' rolls (152.4 m)  
10 rolls per carton

### Approx. Coverage:

375 ft./1000 sq. ft.  
of wallboard  
(114 m/93 sq. m)

## ProForm<sup>®</sup> Fiberglass Joint Tape

---



### Description

A 1.9" wide, self-adhering fiberglass tape for use with Sta-Smooth setting compounds. For use with setting-type compounds only.

Not recommended for use with veneer plaster.

### Packaging

Available in:  
300' rolls (91.4 m)  
12 rolls per carton

### Approx. Coverage:

375 ft./1000 sq. ft.  
of wallboard  
(114 m/93 sq. m)

## ProForm<sup>®</sup> Multi-Flex Tape

---



### Description

A 2" wide combination of joint tape and metal strips laminated to form an outside or inside corner for gypsum wallboard. It is particularly recommended for inside corners on cathedral ceilings, knee-walls, stairways, or any outside or inside corner less or greater than 90°. It is applied with the metal side to the face of the gypsum wallboard and is embedded into the joint compound.

### Packaging

Available in:  
100' rolls (30.5 m)  
10 rolls per carton

### Approx. Coverage:

100 linear feet per roll